

SMART 7 TOUCHSCREEN MONITOR SERIES

Cine 7

The Cinema Flagship 7-inch Monitor
with Camera Control Capability



SMALLHD

SMALLHD
smallhd.com/smart7

CINE 7

The new standard for professional on-set monitoring, combining real-time camera control with a stunning 1800nit, 100% DCI-P3, 1080p display.

SKU MON-CINE7

Premium Display Quality

Cine 7's 1800nit, 1080p display with 100% DCI-P3 color gamut make it the perfect professional monitor for critical eyes.

Integrated Teradek Wireless

Gain total mobility with the Teradek Bolt 4K Transmitter or Receiver modules. Send or receive cable-free wireless video up to 1500ft with zero-delay.

PageOS Software Platform

- Look-Around Camera Control
- EL Zone
- Teradek RT Lens Control Overlays
- Calman® Integration
- Touch Function Buttons
- Horizon Level Indicator

Cinema Camera Control

Unlock access to professional cinema cameras, and tap into project and system settings with intuitive touchscreen configuration tools.* Current supported cameras include ARRI**, RED® **, Sony Venice.

*Camera control licenses sold separately.

**Visit smallhd.com for current camera compatibility.

Please visit our website for the most accurate pricing.



SPECIFICATIONS

HDMI: 1x HDMI In, 1x HDMI Out

SDI: 1x 3G-SDI In, 1x 3G-SDI In/Out

Mounting: 4x 1/4"-20 mounting points

Brightness: 1800nits

Color: 100% DCI-P3 coverage

Power: 2-Pin Power Input
(10 to 34v, 2A DC)

SMART 7 TOUCHSCREEN MONITOR SERIES

Indie 7

The Content Creator 7-inch Monitor
with Camera Control Capability



SMALLHD

SMALLHD

SMALLHD

smallhd.com/smart7

INDIE 7

A vivid, lightweight monitor featuring a responsive touch screen with 1000nits of brightness. Housed in a rugged aluminum chassis, Indie 7 is powered by the user-customizable PageOS 4 software toolset.

SKU MON-INDIE7

Premium Display Quality

Indie 7's 1000nit, 1080p display with 100% Rec. 709 color gamut makes it perfect for professional monitoring.

Integrated Teradek Wireless

Gain total mobility with the Teradek Bolt 4K Transmitter or Receiver modules. Send or receive cable-free wireless video up to 1500ft with zero-delay.

PageOS Software Platform

Utilize SmallHD's dependable imaging software with personalized Page Profile, Frame Guides, Focus & Exposure Assist, Image Capture & Overlay, 3D LUT Control & Storage, Histogram, Vectorscope, 1:1 Pixel Zoom, and more.

Cinema Camera Control

Configure your RED®* in real-time right from the monitor's software interface.**

*Visit smallhd.com for current camera compatibility.

**Camera control licenses sold separately.

Please visit our website for the most accurate pricing.



SPECIFICATIONS

HDMI: 1x HDMI In, 1x HDMI Out

SDI: 1x 3G-SDI In, 1x 3G-SDI In/Out

Mounting: 4x 1/4"-20 mounting points

Brightness: 1000nits

Color: 100% Rec. 709 coverage

Power: Barrel Power Input
(10v to 34v, 2A DC)

SMART 7 TOUCHSCREEN MONITOR SERIES

702 Touch

The Workhorse 7-inch Monitor
with Camera Control Capability



SMALLHD

SMALLHD

SMALLHD

smallhd.com/smart7

702 TOUCH

With a ruggedly built frame, highly visible display, plenty of signal and power options, and world-class software tools, this 7-inch on-camera monitor will make any 1st AC or Director of Photography smile.

SKU MON-702-TOUCH

Premium Display Quality

702 Touch's 1500nit, 1080p display with 100% DCI-P3 color gamut makes it perfect for professional monitoring.

Integrated Teradek Wireless

Gain total mobility with the Teradek Bolt 4K Transmitter or Receiver modules.** Send or receive cable-free wireless video up to 1500ft with zero-delay.

PageOS Software Platform

Utilize SmallHD's dependable imaging software with personalized Page Profile, Frame Guides, Focus & Exposure Assist, Image Capture & Overlay, 3D LUT Control & Storage, Histogram, Vectorscope, 1:1 Pixel Zoom, and more.

Cinema Camera Control

Configure your RED®* in real-time right from the monitor's software interface.**

*Visit smallhd.com for current camera compatibility.

**Features sold separately

Please visit our website for the most accurate pricing.



SPECIFICATIONS

HDMI: 1x HDMI In, 1x HDMI Out

SDI: 1x 3G-SDI In, 1x 3G-SDI In/Out

Mounting: 4x 1/4"-20 mounting points

Brightness: 1500nits

Color: 100% DCI-P3 coverage

Power: Barrel Power Input
(10v to 34v, 2A DC)