Printing date 05/01/2017 Reviewed on 05/01/2017

#### 1 Identification

- · Product identifier
- · Trade name: Drislide Multi-Purpose Lubricant-Liquid
- · Application of the substance / the mixture Lubricant
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Drislide N. America, Inc. 1452 Delashmut Avenue Columbus, OH 43212

Phone: (614) 291-6900 or (800) 231-6901

Cortec Corporation 4119 White Bear Parkway St. Paul, MN 55110 USA Phone (651) 429-1100 Fax (651) 429-1122

- · Information department: (614) 291-6900 or (800) 231-6901
- · Emergency telephone number: 800-231-6901

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Distillates (petroleum), hydrotreated light

· Hazard statements

Flammable liquid and vapor.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

(Contd. on page 2)

Printing date 05/01/2017 Reviewed on 05/01/2017

#### Trade name: Drislide Multi-Purpose Lubricant-Liquid

(Contd. of page 1)

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
	= (r ), j	50-100%	
EINECS: 265-149-8 🗞 Asp. Tox. 1, H304; Flam. Liq. 4, H227			
	Process oil (<3% dimethyl sulfoxide)	≤ 2.5%	
	♦ Asp. Tox. 1, H304; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335		

#### · Additional information

Molybdenum Disulfide is present at 2.5-10%

This product contains mineral oil CAS no. 64742-52-5, which meets EU requirement of less than 3%(w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP346.

In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR 1910.1200), the specific chemical identity and/or exact percentage composition has been withheld as a trade secret.

For the wording of the listed hazard phrases refer to section 16.

### 4 First-aid measures

- · Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact Immediately rinse with water.
- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label

- · Information for doctor Show this safety data sheet to the doctor in attendance.
- · Most important symptoms and effects, both acute and delayed

The symptoms and effects are as expected from the hazards shown in section 2. No specific product related symptoms are known.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

USA

Printing date 05/01/2017 Reviewed on 05/01/2017

Trade name: Drislide Multi-Purpose Lubricant-Liquid

(Contd. of page 2)

### **5** Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents



CO2, sand, extinguishing powder. Do not use water.

· For safety reasons unsuitable extinguishing agents

Water.

Water with full jet.

· Special hazards arising from the substance or mixture

In certain fire conditions, traces of other toxic gases cannot be excluded.

- · Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures





Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- · Environmental precautions: Do not allow undiluted product to enter sewers/surface or ground water
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

- · Handling
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

Printing date 05/01/2017 Reviewed on 05/01/2017

Trade name: Drislide Multi-Purpose Lubricant-Liquid

(Contd. of page 3)

Use explosion-proof apparatus / fittings and spark-proof tools.

- · Conditions for safe storage, including any incompatibilities
- ·Storage
- · Requirements to be met by storerooms and receptacles:

Use only receptacles specifically permitted for this substance/product.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

64742-47-8	64742-47-8 Distillates (petroleum), hydrotreated light (50-100%)		
RCP-TWA	RCP-TWA Long-term value: 1200 mg/m <sup>3</sup>		
	Total Hydrocarbons		
Distillates (	Distillates (petroleum), hydrotreated heavy naphthenic (2.5-10%)		
OEL	Short-term value: 5 mg/m³, 5 ppm		

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls Use local exhaust ventilation to control airborne concentrations below exposure limits.
- · Personal protective equipment
- · General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Breathing equipment:



Use suitable respiratory protective device in case of insufficient ventilation.

Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). To determine the appropriate type of respiratory protection that should be used, a hazard assessment should be performed prior to using the product. Environmental conditions such as ventilation and other contaminants may affect the type of respiratory protection that is chosen.

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Protective Gloves I.E., Nitrile, Viton, Neoprene

(Contd. on page 5)

Printing date 05/01/2017 Reviewed on 05/01/2017

Trade name: Drislide Multi-Purpose Lubricant-Liquid

· Penetration time of glove material

(Contd. of page 4)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Tightly sealed goggles. Body protection: Protective work clothing.

Physical and chemical proper	ties
Information on basic physical and c General Information Appearance:	hemical properties
Form:	Liquid
Color:	Black
· Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	undetermined
<b>Boiling point/Boiling range:</b>	175 °C (347 °F) (*)
Flash point:	46 °C (115 °F) (*)
Flammability (solid, gaseous)	Not applicable.
Ignition temperature:	210 °C (410 °F) (*)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap-mixtures are possible.
Explosion limits:	
Lower:	0.5 Vol % (*)
Upper:	6.5 Vol % (*)
Vapor pressure at 20 °C (68 °F):	2 hPa (2 mm Hg) (*)
Density at 20 °C (68 °F):	0.72-0.96 g/cm³ (6.008-8.011 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
Other information	VOC: 0.72 g/cm3 (6.01 lb/gal)
	The above data are typical values and do not constitute a specification *Properties have been calculated.

Printing date 05/01/2017 Reviewed on 05/01/2017

Trade name: Drislide Multi-Purpose Lubricant-Liquid

(Contd. of page 5)

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under recommended storage conditions
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known
- · Conditions to avoid No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC	· LD/LC50 values that are relevant for classification:			
64742-4	64742-47-8 Distillates (petroleum), hydrotreated light			
Oral	LD50	>5000 mg/kg (Rat)		
Dermal	LD50	>2000 mg/kg (Rabbit)		
Process oil (<3% dimethyl sulfoxide)				
Oral	LD50	>2000 mg/kg (rat)		

- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

IARC Category 3: Not classifiable as to its carcinogenicity to humans

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

#### 64742-47-8 Distillates (petroleum), hydrotreated light

Oral LL50 25 mg/l (Oncorhynchus mykiss (rainbow trout)) (96 hours) LC50 2.9 mg/l (Oncorhynchus mykiss (rainbow trout)) (96 hours)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 7)

(Contd. of page 6)

## **Safety Data Sheet** acc. to OSHA HCS

Printing date 05/01/2017 Reviewed on 05/01/2017

Trade name: Drislide Multi-Purpose Lubricant-Liquid

· Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation Dispose of in accordance with local, state, and federal regulations.
- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

4 7	7				
 	Trom	CITA		nmma	TOB
1 1		NILL	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	 orma	

· UN-Number · DOT, ADR, IMDG, IATA	UN1993
· UN proper shipping name	
· DOT	Flammable liquids, n.o.s. (Distillates (petroleum), hydrotreated
	light)
· ADR	1993 Flammable liquids, n.o.s. (Distillates (petroleum),
	hydrotreated light)
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Distillates (petroleum),

hydrotreated light)

- · Transport hazard class(es)
- $\cdot\, DOT$



3 Flammable liquids · Class ·Label

· ADR, IMDG, IATA



3 Flammable liquids · Class ·Label

· Packing group

· DOT, ADR, IMDG, IATA III

· Environmental hazards: Not applicable. Warning: Flammable liquids · Special precautions for user

· Danger code (Kemler): 30 · EMS Number: F-E,S-E

· Stowage Category

(Contd. on page 8)

Printing date 05/01/2017 Reviewed on 05/01/2017

Trade name: Drislide Multi-Purpose Lubricant-Liquid

	(Contd. of page
· Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Excepted quantities (EQ)	Code: E1
• • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
• •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (DISTILLATE
-	(PETROLEUM), HYDROTREATED LIGHT), 3, III

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · SARA Section 355 (extremely hazardous substances)

None of the ingredients is listed.

· SARA Section 313 (specific toxic chemical listings)

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act) (Substances not listed)

Process oil (<3% dimethyl sulfoxide)

· Prop 65 - Chemicals known to cause cancer

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Canadian Domestic Substances List (DSL) (Substances not listed)

All ingredients are listed.

· Philippines Inventory of Chemicals and Chemical Substances (Substances not listed)

All ingredients are listed.

· Chinese Chemical Inventory of Existing Chemical Substances (Substances not listed)

All ingredients are listed.

· Australian Inventory of Chemical Substances (Substances not listed)

All ingredients are listed.

· New Zealand Inventory of Chemicals (Substances not listed)

Distillates (petroleum), hydrotreated light

Distillates (petroleum), solvent-refined light paraffinic

(Contd. on page 9)

Printing date 05/01/2017 Reviewed on 05/01/2017

Trade name: Drislide Multi-Purpose Lubricant-Liquid

(Contd. of page 8)

Distillates (petroleum), solvent-dewaxed heavy paraffinic

### · Existing Chemical Substances (Substances not listed)

Distillates (petroleum), hydrotreated light

Graphite

Distillates (petroleum), solvent-refined light paraffinic

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02 GH

- · Signal word Danger
- · Hazard-determining components of labeling:

Distillates (petroleum), hydrotreated light

· Hazard statements

Flammable liquid and vapor.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Cortec Corporation does not warranty any translation of this SDS not created by Cortec Corporation.

- · Date of preparation / last revision 05/01/2017 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 10)

Printing date 05/01/2017 Reviewed on 05/01/2017

### Trade name: Drislide Multi-Purpose Lubricant-Liquid

(Contd. of page 9)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 3: Flammable liquids – Category 5
Flam. Liq. 4: Flammable liquids – Category 4
Acute Tox. 4: Acute toxicity – Category 4
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1

\* Data compared to the previous version altered.