



PLAYER DRIVEN. TOUR PROVEN.

## **PARALLEL TIP TRIMMING**

**THE KBS TOUR, TGI, TOUR 105, TOUR 90, C-TAPER, C-TAPER LITE AND KBS 560/580 CAN BE PURCHASED IN TAPER TIP (.355) AND PARALLEL TIP (.370). LISTED BELOW ARE THE TRIMMING INSTRUCTIONS FOR THE PARALLEL TIP SHAFTS. THIS ALLOWS THE CLUB MAKER TO ACHIEVE DIFFERENT FLEX AND PERFORMANCE.**



### STEP 1. SELECT YOUR SHAFT AND DESIRED FREQUENCY

	SOFTTEST → STIFFEST			
TOUR R FLEX, 120g	4.0 FREQ	4.5 FREQ	5.0 FREQ	5.5 FREQ
TOUR S FLEX, 130g	5.0 FREQ	5.5 FREQ	6.0 FREQ	6.5 FREQ
TOUR X FLEX, 133g	6.0 FREQ	6.5 FREQ	7.0 FREQ	7.5 FREQ

### STEP 2. SHAFT TRIMMING SPECIFICATIONS

1-IRON	0"	7/8"	1 7/8"	2 7/8"
2-IRON	7/16"	1 7/16"	2 7/16"	3 7/16"
3-IRON	1"	2"	3"	4"
4-IRON	1 9/16"	2 9/16"	3 9/16"	4 9/16"
5-IRON	2 1/8"	3 1/8"	4 1/8"	5 1/8"
6-IRON	2 11/16"	3 11/16"	4 11/16"	5 11/16"
7-IRON	3 1/4"	4 1/4"	5 1/4"	6 1/4"
8-IRON	3 13/16"	4 13/16"	5 13/16"	6 13/16"
9-IRON	4 3/8"	5 3/8"	6 3/8"	7 3/8"
PW	4 15/16"	5 15/16"	6 15/16"	7 15/16"

### PERFORMANCE CHART

FLEX	ACHIEVABLE RANGE
REGULAR	4.0 fm - 5.5 fm
STIFF	5.0 fm - 6.5 fm
X-STIFF	6.0 fm - 7.5 fm



### STEP 1. SELECT YOUR SHAFT AND DESIRED FREQUENCY

	SOFTTEST → STIFFEST		
TOUR 90 R FLEX, 101g	3.0 FREQ	3.5 FREQ	4.0 FREQ
TOUR 90 S FLEX, 102g	4.0 FREQ	4.5 FREQ	5.0 FREQ

### STEP 2. SHAFT TRIMMING SPECIFICATIONS

4-IRON	0"	1 1/2"	3"
5-IRON	1/2"	2"	3 1/2"
6-IRON	1"	2 1/2"	4"
7-IRON	1 1/2"	3"	4 1/2"
8-IRON	2"	3 1/2"	5"
9-IRON	2 1/2"	4"	5 1/2"
PW	2 1/2"	4"	5 1/2"

### PERFORMANCE CHART

FLEX	ACHIEVABLE RANGE
REGULAR	3.0 fm - 4.0 fm
STIFF	4.0 fm - 5.0 fm

# KBS C-TAPER by FST

## STEP 1. SELECT YOUR SHAFT AND DESIRED FREQUENCY

	SOFTEST	—————→			STIFFEST
C-TAPER R FLEX, 125g	3.5 FREQ	4.0 FREQ	4.5 FREQ	5.0 FREQ	
C-TAPER S FLEX, 135g	4.5 FREQ	5.0 FREQ	5.5 FREQ	6.0 FREQ	
C-TAPER X FLEX, 140g	5.5 FREQ	6.0 FREQ	6.5 FREQ	7.0 FREQ	

## STEP 2. SHAFT TRIMMING SPECIFICATIONS

1-IRON	3/16"	1 3/16"	2 3/16"	3 3/16"
2-IRON	3/4"	1 3/4"	2 3/4"	3 3/4"
3-IRON	1 5/16"	2 5/16"	3 5/16"	4 5/16"
4-IRON	1 7/8"	2 7/8"	3 7/8"	4 7/8"
5-IRON	2 7/16"	3 7/16"	4 7/16"	5 7/16"
6-IRON	3"	4"	5"	6"
7-IRON	3 9/16"	4 9/16"	5 9/16"	6 9/16"
8-IRON	4 1/8"	5 1/8"	6 1/8"	7 1/8"
9-IRON	4 11/16"	5 11/16"	6 11/16"	7 11/16"
PW	5 1/4"	6 1/4"	7 1/4"	8 1/4"

## PERFORMANCE CHART

FLEX	ACHIEVABLE RANGE
REGULAR	3.5 fm - 5.0 fm
STIFF	4.5 fm - 6.0 fm
X-STIFF	5.5 fm - 7.0 fm

# KBS C-TAPER LITE by FST

## STEP 1. SELECT YOUR SHAFT AND DESIRED FREQUENCY

	SOFTEST	—————→			STIFFEST
C-TAPER LITE R FLEX, 108.5g	4.0 FREQ			4.5 FREQ	
C-TAPER LITE S FLEX, 118.5g	4.5 FREQ			5.0 FREQ	
C-TAPER LITE X FLEX, 125g	5.0 FREQ			5.5 FREQ	

## STEP 2. SHAFT TRIMMING SPECIFICATIONS

1-IRON	1/2"			1 1/2"
2-IRON	1"			2"
3-IRON	1 1/2"			2 1/2"
4-IRON	2"			3"
5-IRON	2 1/2"			3 1/2"
6-IRON	3"			4"
7-IRON	3 1/2"			4 1/2"
8-IRON	4"			5"
9-IRON	4 1/2"			5 1/2"
PW	4 1/2"			5 1/2"

## PERFORMANCE CHART

FLEX	ACHIEVABLE RANGE
REGULAR	4.0 fm - 4.5 fm
STIFF	4.5 fm - 5.0 fm
X-STIFF	5.0 fm - 5.5 fm

# KBS TOUR 560<sup>by FST</sup>

## STEP 1. ANALYSIS

	GRAPHITE	STEEL
RIGHT TO LEFT (RIGHT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL
LEFT TO RIGHT (RIGHT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL
RIGHT TO LEFT (LEFT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL
LEFT TO RIGHT (LEFT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL

## STEP 2. SELECT SHAFT FLEX

REGULAR

STIFF

## STEP 3. TIP TRIM SHAFT

	TIP TRIM (IN.)	LENGTH (IN.)	TIP TRIM (IN.)	LENGTH (IN.)
3-IRON			1"	36 1/2"
4-IRON	0"	36"	1 1/2"	36"
5-IRON	1/2"	35 1/2"	2"	35 1/2"
6-IRON	1"	35"	2 1/2"	35"
7-IRON	1 1/2"	34 1/2"	3"	34 1/2"
8-IRON	2"	34"	3 1/2"	34"
9-IRON	2 1/2"	33 1/2"	4"	33 1/2"
PW	3"	33"	4 1/2"	33"

# KBS TOUR 580<sup>by FST</sup>

## STEP 1. ANALYSIS

	GRAPHITE	STEEL
RIGHT TO LEFT (RIGHT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL
LEFT TO RIGHT (RIGHT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL
RIGHT TO LEFT (LEFT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL
LEFT TO RIGHT (LEFT-HANDED)	START WITH 560 MODEL	START WITH 580 MODEL

## STEP 2. SELECT SHAFT FLEX

REGULAR

STIFF

## STEP 3. TIP TRIM SHAFT

	TIP TRIM (IN.)	LENGTH (IN.)	TIP TRIM (IN.)	LENGTH (IN.)
3-IRON			1"	36 1/2"
4-IRON	0"	36"	1 1/2"	36"
5-IRON	1/2"	35 1/2"	2"	35 1/2"
6-IRON	1"	35"	2 1/2"	35"
7-IRON	1 1/2"	34 1/2"	3"	34 1/2"
8-IRON	2"	34"	3 1/2"	34"
9-IRON	2 1/2"	33 1/2"	4"	33 1/2"
PW	3"	33"	4 1/2"	33"



# KBS TOUR 105 by FST

## STEP 1. SELECT YOUR SHAFT AND DESIRED FREQUENCY

	SOFTTEST <span style="float: right;">→</span>	STIFFEST
TOUR 105 R FLEX, 109g	3.0 FREQ	4.5 FREQ
TOUR 105 S FLEX, 114g	4.0 FREQ	5.5 FREQ
TOUR 105 X FLEX, 119g	5.0 FREQ	6.5 FREQ

## STEP 2. SHAFT TRIMMING SPECIFICATIONS

3-IRON	1"	2"
4-IRON	1 1/2"	2 1/2"
5-IRON	2"	3"
6-IRON	2 1/2"	3 1/2"
7-IRON	3"	4"
8-IRON	3 1/2"	4 1/2"
9-IRON	4"	5"
PW	4 1/2"	5 1/2"

## PERFORMANCE CHART

FLEX	ACHIEVABLE RANGE
REGULAR	3.0 fm - 4.5 fm
STIFF	4.0 fm - 5.5 fm
X-STIFF	5.0 fm - 6.5 fm

# KBS MAX 80 by FST

## STEP 1. SELECT SHAFT FLEX

REGULAR

STIFF

X-STIFF

## STEP 2. TIP TRIM SHAFT

	REGULAR		STIFF		X-STIFF	
	TIP TRIM (IN.)	LENGTH (IN.)	TIP TRIM (IN.)	LENGTH (IN.)	TIP TRIM (IN.)	LENGTH (IN.)
3-IRON	1"	41"	2"	40"	3"	39"
4-IRON	1 1/2"	40 1/2"	2 1/2"	39 1/2"	3 1/2"	38 1/2"
5-IRON	2"	40"	3"	39"	4"	38"
6-IRON	2 1/2"	39 1/2"	3 1/2"	38 1/2"	4 1/2"	37 1/2"
7-IRON	3"	39"	4"	38"	5"	37"
8-IRON	3 1/2"	38 1/2"	4 1/2"	37 1/2"	5 1/2"	36 1/2"
9-IRON	4"	38"	5"	37"	6"	36"
PW	4"	38"	5"	37"	6"	36"

# KBS \$-TAPER LITE <sup>by FST</sup>

## STEP 1. SELECT YOUR SHAFT AND DESIRED FREQUENCY

	SOFTEST		STIFFEST
\$-TAPER LITE R FLEX, 110g	3.0 FREQ	3.5 FREQ	4.0 FREQ
\$-TAPER LITE S FLEX, 115g	4.0 FREQ	4.5 FREQ	5.0 FREQ
\$-TAPER LITE X FLEX, 120g	5.0 FREQ	5.5 FREQ	6.0 FREQ

## STEP 2. SHAFT TRIMMING SPECIFICATIONS

3-IRON	1/2"	1 1/2"	2 1/2"
4-IRON	1"	2"	3"
5-IRON	1 1/2"	2 1/2"	3 1/2"
6-IRON	2"	3"	4"
7-IRON	2 1/2"	3 1/2"	4 1/2"
8-IRON	3"	4"	5"
9-IRON	3 1/2"	4 1/2"	5 1/2"
PW	3 1/2"	4 1/2"	5 1/2"

## PERFORMANCE CHART

FLEX	ACHIEVABLE RANGE
REGULAR	3.0 fm - 4.0 fm
STIFF	4.0 fm - 5.0 fm
X-STIFF	5.0 fm - 6.0 fm

# KBS TOUR GRAPHITE IRON <sup>by FST</sup>

	80g - 4.0 FREQ	70g - 3.0 FREQ	60g - 2.0 FREQ	50g - 1.0 FREQ
3-IRON	1/2"	1/2"	1/2"	1/2"
4-IRON	1"	1"	1"	1"
5-IRON	1 1/2"	1 1/2"	1 1/2"	1 1/2"
6-IRON	2"	2"	2"	2"
7-IRON	2 1/2"	2 1/2"	2 1/2"	2 1/2"
8-IRON	3 "	3 "	3 "	3 "
9-IRON	3 1/2"	3 1/2"	3 1/2"	3 1/2"
PW	3 1/2"	3 1/2"	3 1/2"	3 1/2"

# KBS MAX GRAPHITE IRON <sup>by FST</sup>

	85g - 3.0 FREQ	75g - 2.0 FREQ	65g - 1.0 FREQ	55g - 0 FREQ	45g - -1.5 FREQ
3-IRON	1/2"	1/2"	1/2"	1/2"	1/2"
4-IRON	1"	1"	1"	1"	1"
5-IRON	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
6-IRON	2"	2"	2"	2"	2"
7-IRON	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"
8-IRON	3 "	3 "	3 "	3 "	3 "
9-IRON	3 1/2"	3 1/2"	3 1/2"	3 1/2"	3 1/2"
PW	3 1/2"	3 1/2"	3 1/2"	3 1/2"	3 1/2"