



Technical data

	20	50	60	70
Airwatts	506 AW	506 AW	600 AW	666 AW
Water Lift (H ₂ O)	106.4" - 2692 mm	106.4" - 2692 mm	119.7" - 3022 mm	122.2" - 3099 mm
Decibels	54 db	54 db	64 db	64 db
Air flow	105 CFM - 179 CMH	105 CFM - 179 CMH	118 CFM - 201 CMH	122 CFM - 207 CMH
MAX amps	12.8 A	12.8 A	12.8 A	14.7 A
Voltage	120 V	120 V	120 V	120 V
Number of motors	1	1	1	1
Turbines per motor	1	1	1	1
Bag capacity	6.4 l 1.7 gal US	20 l 5.3 gal US	20 l 5.3 gal US	20 l 5.3 gal US
Canister capacity	n/a	17.4 l 4.6 gal US	17.4 l 4.6 gal US	17.4 l 4.6 gal US
Weight	5.9 kg 11 lbs	10.2 kg 22.4 lbs	10.2 kg 22.4 lbs	10.2 kg 22.4 lbs
Height	36.8 cm 14.2"	95.2 cm 37.4"	95.2 cm 37.4"	95.2 cm 37.4"
Diameter	26.7 cm 10.2"	30.2 cm 11.9"	30.2 cm 11.9"	30.2 cm 11.9"
Principle	Electrostatic bag	Bag or self-cleaning filter		
Filtration	Permanent filter	Hybrid filtration		
Part warranty†	10 years*			
Labor warranty†	3 years			
Product Code	ASUPERV20A	ASUPERV50A	ASUPERV60A	ASUPERV70A