



QM-LX13M: 13 oz. matte frontlit fire retardant scrim banner

Unlike most scrim banner on the market, LX13M was developed to be extremely durable and work across Latex, Eco-Solvent and UV platforms. Its high tensile strength 1000 x 1000 denier scrim, makes for a very tear resistant banner. The fire retardant coating allows it to be used in all environments.



Benefits:

- Fire Retardant
- 1000 x 1000 Denier
- Scratch Resistant
- Durable

Applications:

- Frontlit Banners
- Display Systems
- Grommated Banners
- POP Display

Registered Latex Developer

TECHNICAL DATA: QM-LX13M – 13 OZ. MATTE FRONTLIT FIRE RETARDANT SCRIM BANNER

SURFACE FINISH:	Matte	OPACITY:	100
BASE MATERIAL:	PVC	DURABILITY:	<i>Indoor:</i> Up to 1 year <i>Outdoor:</i> Up to 6 months
BASE WEIGHT:	(13 oz.) 440 GSM +/- 10%	ROLL LENGTH:	150 FT.
CALIPER:	15 Mil +/- 1	ROLL WIDTHS:	38" 54" & 60"
BRIGHTNESS:	85 (ISO Blue Whiteness)	CORE:	3"
WHITENESS:	116 (CIE Ganz)	PRINT SIDE:	Print Side Out
GLOSS MEASUREMENT	6 +/- 10% by angle of 60°	INK RECOMMENDATIONS:	ECO-SOLVENT LATEX UV
STORAGE: Up to six months if stored in proper conditions (cool, dry place 50-80°)			



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)

