



QM-WRMVAD: Matte WR vinyl w/ permanent adhesive

With its stay-flat PE coated liner and our signature matte porous coating, this is sure to be your go-to. Best for any mounted application where tight curves and clean cutting need to be addressed. Highly water resistant and instant dry times for faster production.



Benefits:

- Water Resistant
- Instant Dry Coating
- Accepts Heavy Ink Loads

Applications:

- Best for Curved Mounting or Print and Cut
- Decals
- Boards

TECHNICAL DATA: QM-WRMVAD – MATTE WR VINYL W/ ADHESIVE

SURFACE FINISH:	Matte	WHITENESS:	148 (CIE Ganz)
BASE MATERIAL:	PVC	OPACITY:	95
ADHESIVE:	Clear Acrylic	GLOSS MEASUREMENT:	3 +/- 10 by Angle of 60°
LINER MATERIAL:	Double Side PE Coated	DURABILITY:	<i>Indoor:</i> Up to 1 year <i>Outdoor:</i> Up to 6 months
LINER WEIGHT:	155 GSM +/- 10%	ROLL LENGTH:	100 FT.
LINER THICKNESS:	6 Mil +/- 1	ROLL WIDTHS:	24", 36", 42", 50" & 60"
FACE STOCK WEIGHT:	175 GSM +/- 10%	CORE:	2"
FACE STOCK THICKNESS:	6 Mil +/- 1	PRINT SIDE:	Print Side Out
BRIGHTNESS:	105 (ISO Blue Whiteness)	INK RECOMMENDATIONS:	AQUEOUS



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

