

**NEW LUX  
ANTI  
SCRATCH  
COATING**



## QM-SWRPPBOLUX: Hybrid satin lux blockout stay-flat polypropylene

Bright white anti-scratch satin top coating for bright color graphic printing. The block-out layer give your graphic “POP” with no wash-out from the backside. The back side coating creates a economical product with good stay-flat qualities. The perfect solution to short-term trade show displays and posters.



### Benefits:

- Instant Dry Coating
- Scratch/Tear Resistant
- Lamination Not Needed
- 100% Opaque
- Water Resistant

### Applications:

- Durable Posters
- Trade Show Display
- Low Cost Roll-Up

Registered Latex Developer



#### TECHNICAL DATA: QM-SWRPPBOLUX – HYBRID SATIN LUX BLOCKOUT STAY-FLAT POLYPROPYLENE

SURFACE FINISH:	Satin	OPACITY:	100
BASE MATERIAL:	Polypropylene	DURABILITY:	Indoor: Up to 1 year Outdoor: Up to 6 months
BASE WEIGHT:	153 GSM +/- 10%	ROLL LENGTH:	100 FT.
CALIPER:	8 Mil +/- 1	ROLL WIDTHS:	36", 60"
BRIGHTNESS:	90 (ISO Blue Whiteness)	CORE:	3"
WHITENESS:	93 (CIE Ganz)	PRINT SIDE:	Print Side Out
GLOSS MEASUREMENT	13 +/- 10% by angle of 60°	INK RECOMMENDATIONS:	ES ECOSOLVENT L LATEX UV UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

