90cm Curved Glass Canopy
RANGEHOOD

PRODUCT CODE: **EAGL90SX**

3 YEARS Warranty

HELPFUL TIPS

+ Leave your rangehood on for 15 minutes after the cooking of the food to remove all odors, steam etc.
+ The dishwasher-safe cassette filters need to be cleaned after approximately 2 months of standard operation
+ It is recommended that the rangehood be installed between 650mm and 750mm above the cooktop
+ It is also recommended that fumes from the rangehood be ducted out into the atmosphere.
+ Turn off the rangehood before attempting to clean

FEATURES:

+ Stainless steel + glass finish
+ 3 speed motor
+ 700m³ / hr extraction capacity
+ 2 x 0.5W LED lights
+ Separate light function

+ Tempered curved glass design
+ Electronic button front controls
+ LCD display
+ Dishwasher safe cassette filters
+ 150mm air flow outlet

INSTALLATION

Installation is recommended by a qualified installer, please refer to the product manual for full installation instructions.

FILTER CLEANING INFORMATION

Cassette mesh filter: Requires cleaning monthly. This will ensure no interruptions with airflow operation.

LCD DISPLAY CONTROL
The stunning blue LCD display provides the Rangehoods with a stylish appearance. This feature displays extraction speeds plus the time of day.

3 SPEED MOTOR
This rangehood provides the option of 3 different speed levels ensuring you have the option to use your rangehood at a low, medium or high level of operation.

HIGH EXTRACTION CAPACITY
The extraction capacity of 700m3/hr provides strength and power to this stylish rangehood.

DISHWASHER SAFE CASSETTE FILTERS
The cassette filters can be placed in a dishwasher for easy cleaning and can easily be removed, re-connected from the rangehood.

DECIBEL RATING
54-60 dBA

Electrical Requirements	Rangehood is supplied with 10amp cord & plug.
Available Ventilation Kits	
RHKE65	Wall – Eave vent kit
RHKMR65	Universal metal roof kit (includes flashing)
RHKTR65	Universal tile roof kit (includes flashing)
Rangehood Extensions	Flue Extensions 1m Code: ERGLEXT
Carbon Filter	CF110 (requires 2)
Barcode	**9347726028866**

305 273
560–1040 560 Φ150 30 210 80
380 570 900 500