



## Technical Details

#### Style

Rangehood Type: Fixed Category Size: 60cm

#### **Functionality**

Extraction Type: Ducted or

Front Recirculating
Extraction Rate: 333m³/hr Net
440m³/hr Gross

Number of Motors: 2
Watts of Motor: 100w
Speeds: 3

Filtration: 2 x Aluminium Mesh

Lights: 1 x 2W LED dBA Rating: 48-56dBA

#### Accessories

Charcoal Filter: Optional (ORCF110 x 2)

## Installation

Maximum Current: 3 Pin Plug
Connection: 220 - 240V, 50Hz
Installation Type Built-in to


Overhead Cabinetry

Warranty: 24 Months Parts & Labour

# Dimensions/Weight

Overall Dimensions (mm):  $150(h) \times 600(w) \times 500(d)$ 

Flue Diameter (mm): 120mm Weight: 7.5kg



## **Aesthetics**

Finish: Brushed Stainless Steel
Controls: Push Buttons

## **Key Features**



#### Front Recirculation

Sometimes it's not possible to duct your rangehood. If that's the case, then it's likely you'll need a recirculating Omega hood. These cleverly designed appliances draw the grease laden smoke and steam air inside the unit before cleaning and purify it — then sending it back as fresh air through the front panel. And, because there's no ducting, you can be up and running in no time.



## Washable Filter

The removable, washable filter is easy to maintain and keep clean ensuring your rangehood always performs well.



#### Shallow Height

This rangehood has a shallow height meaning it is perfect for an areas with low overhead cupboards plus at only 60cm wide means it is perfect for smaller cooktops and spaces.



T: 1300 739 033 (AU)

09 415 6000 (NZ)

E: customercare@omegaappliances.com.au customercare@monacocorp.co.nz

