

OC EVD-40D

Ocular EV DC Charging Station

OCULAR



LEADING - EDGE TECHNOLOGY

Large capacity DC charger for public charging station, CCS/CHAdemo plugs

Features

 Programmable charging mode

 7" touch screen

 Comprehensive protection

 Australian standard

 Multiple communication modes

 Dual output ports

Datasheet

OC EVD-40D

Input & Output

Input voltage	260~530V AC
Rated input voltage	400V AC
Frequency	50Hz/60Hz
DC plug type	CCS Type 2 x 2, CHAdeMO, double plugs
Output voltage range	CCS(150-750V), CHAdeMO(150-500V)
Max. output power	40kW
Max. output current	CCS 80A, CHAdeMO 80A
Voltage accuracy	<±0.5%
Current accuracy	≤±1%(at 20%~100% of rated power)
Voltage-regulating accuracy	<±0.5%
Current-regulating accuracy	≤±1%
Ripple coefficient	RMS: ≤±0.5%; Peak: ≤±1%
Metering accuracy	0.5%
Efficiency	≥95.2%
Cable Length	5m

Protection

Over voltage protection	Yes
Under voltage protection	Yes
Over load protection	Yes
Short circuit protection	Yes
Earth leakage protection	Yes
Over-temp protection	Yes
Lightning protection	Yes
RCD protection	TypeB

Function & Accessory

Display	7 inch touch screen
Ethernet/WIFI/4G	Yes/Opt/Opt
Payment support	RFID/QR(standard)
Indicator	Yes
Emergency stop	Yes

Working Environment

Protection degree	IP54
Operating temperature	-20°C ~+50°C
Relative humidity	5%-95% non-condensing
Maximum altitude	2000m
Cooling	Forced air cooling
Standby power consumption	<25W
Noise emission	≤65db

Mechanical

Dimension (W/H/D)	558/775/298mm
Weight	90KG

Certificate

Certificate	CE, RCM
-------------	---------