

## Notes:

- Maximum Electric Current: 

|     |    |    |  |  |
|-----|----|----|--|--|
| AWG | 16 | 14 |  |  |
| AMP | 10 | 15 |  |  |
- Maximum Electrical Rating: 105° 600 Volts Max.
- Insulation Material: Vinyl
- Insulation Color: Blue
- Terminal Material: Brass
- Wire Range: 16-14 AWG (1.5-2.5mm<sup>2</sup>)
- Terminal Surface Treatment: Tin Plated
- Nema Tab: 0.032" x 0.187" (0.8mm x 4.75mm)
- Double Crimp
- Terminal Thickness: 0.35mm

### Standard (Metric)

0.76" (19.4mm)  
 0.41" (10.5mm)  
 0.25" (6.4mm)  
 0.20" (5mm)  
 0.09" (2.3mm)  
 0.19" (4.7mm)

### Tolerances

(Unless Otherwise Specified)

0 > 6mm ± 0.20  
 6 > 18mm ± 0.30  
 18 > 30mm ± 0.40  
 30 > 75mm ± 0.50

| CATEGORY | Female Vinyl Insulated<br>Double Crimp Disconnects | SCALE | 4/1  |
|----------|--|-------|------|
| PART #   | FDD2-187(8)  | SHEET | 1-1  |
| MATERIAL | Tin-Plated Brass                                   | PAGE  | 10F2 |



**FerrulesDirect**

