

## Notes:

- Maximum Electric Current: 

|     |    |    |  |
|-----|----|----|--|
| AWG | 16 | 14 |  |
| AMP | 10 | 15 |  |
- Terminal Material: Brass
- Insulation Material: Nylon
- Insulation Color: Blue
- Maximum Electrical Rating: 105° 600 Volts Max.
- Wire Range: 16-14 AWG (1.5-2.5mm<sup>2</sup>)
- Terminal Surface Treatment: Tin Plated
- Terminal Thickness: 0.40mm

## Standard (Metric)

0.95" (24.2mm)  
0.43" (11mm)  
0.43" (10.8mm)  
0.18" (4.5mm)  
0.09" (2.3mm)  
0.18" (4.5mm)

## Tolerances

(Unless Otherwise Specified)

0 > 6mm ± 0.20  
6 > 18mm ± 0.30  
18 > 30mm ± 0.40  
30 > 75mm ± 0.50

|          |                                          |       |      |
|----------|------------------------------------------|-------|------|
| CATEGORY | Nylon Insulated<br>Male Bullet Connector | SCALE | 4/1  |
| PART #   | MPNYL2-180                               | SHEET | 1-2  |
| MATERIAL | Tin-Plated Brass                         | PAGE  | 10F2 |



FerrulesDirect

