

Nylon Cable Ties - Standard Specifications



Material

UL approved 94UV-2 Nylon 6/6

Gamma Resistance: 1x10 Rads

Service Temperature: -40°F to 185°F (-40°C to 85°C)

Product Description

Standard nylon cable ties are the definition of simple yet effective. They perfectly serve as both a fastening and bundling item. They are used in a wide variety of general applications and can even be used to bundle up wires and cables to tidy up your workspace.

Length (mm)	Stock #	WxL (mm)	WxL (In)	Tensile Strength (lbs)	Tensile Strength (kg)	Thickness (In/mm)	Bundle Diameter (mm)	Bundle Diameter (In)	Qty
75	CT075	2.5x75	0.10x3.0	18	8.20	0.04/1.06	18	0.71	100
80	CT080	2.5x80	0.10x3.2	18	8.20	0.04/1.06	16	0.63	100
94	CT094	2.5x94	0.10x3.7	18	8.20	0.04/1.06	22	0.86	100
100	CT100	2.5x100	0.10x4.0	18	8.20	0.04/1.06	22	0.86	100
120	CT120S	2.5x100	0.10x4.0	18	8.20	0.04/1.06	22	0.86	100
120	CT120	2.5x100	0.10x4.0	18	8.20	0.04/1.06	22	0.86	100
120	CT120L	4.8x120	0.19x4.7	50	22.70	0.05/1.32	27	1.06	100
140	CT140	3.2x140	0.13x5.5	40	18.10	0.04/1.24	34	1.34	100
150	CT150S	2.5x150	0.10x6.0	18	8.20	0.04/1.06	39	1.54	100
150	CT150	3.6x150	0.14x6.0	40	18.10	0.04/1.06	36	1.41	100
160	CT160	2.5x160	0.10x6.3	18	8.20	0.04/1.06	43	1.69	100
160	CT160L	4.8x160	0.19x6.3	50	22.70	0.05/1.32	39	1.54	100
180	CT180	3.6x180	0.14x7.1	40	18.10	0.04/1.24	46	1.81	100
200	CT200	4.8x200	0.18x7.87	50	22.67	0.04/1.06	49.50	1.94	100
200	CT200M	2.5x203	0.10x8.0	18	8.20	0.04/1.06	55	2.16	100
200	CT200L	7.6x203	0.30x8.0	120	54.40	0.07/1.93	55	2.16	100
200	CT200A	3.6x203	0.14x8.0	40	18.10	0.04/1.24	55	2.16	100
250	CT250S	2.5x250	0.10x10.0	18	8.20	0.04/1.06	68	2.68	100
250	CT250	4.8x250	0.19x10.0	50	22.70	0.05/1.32	68	2.68	100
280	CT280	4.8x280	0.19x11.0	50	22.70	0.05/1.32	77	3.03	100

Length (mm)	Stock #	WxL (mm)	WxL (In)	Tensile Strength (lbs)	Tensile Strength (kg)	Thickness (In/mm)	Bundle Diameter (mm)	Bundle Diameter (In)	Qty
300	CT300S	4.8x300	0.19x12	50	22.70	0.07/1.93	83	3.27	100
300	CT300	7.6x300	0.30x12	120	54.40	0.07/1.93	80	3.15	100
300	CT300M	3.6x300	0.14x12	40	18.10	0.04/1.24	82	3.23	100
350	CT350	4.8x350	0.19x13.7	50	22.70	0.05/1.32	97	3.81	100
360	CT360	4.8x350	0.19x13.7	50	22.70	0.05/1.32	97	3.81	100
370	CT370S	3.6x370	0.14x14.5	40	18.10	0.04/1.24	105	4.13	100
370	CT370	4.8x370	0.19x14.5	50	22.70	0.05/1.32	105	4.13	100
380	CT380	7.6x380	0.30x15.0	120	54.40	0.07/1.93	105	4.13	100
385	CT385	4.8x385	0.19x15.2	50	22.70	0.05/1.32	110	4.33	100
400	CT400	4.8x400	0.19x15.7	50	22.70	0.05/1.32	113	4.44	100
432	CT432	4.8x432	0.19x17.0	50	22.70	0.05/1.32	125	4.92	100
500	CT500	4.8x500	0.19x19.7	50	22.70	0.05/1.32	140	5.50	100
500	CT500L	7.6x500	0.30x19.7	120	54.40	0.07/1.93	150	5.90	100
550	CT550S	4.8x550	0.19x21.7	50	22.70	0.05/1.32	162	6.38	100
550	CT550	8.0x550	0.31x21.7	175	79.40	0.09/2.29	160	6.30	100
610	CT610S	4.8x610	0.19x24.0	50	22.70	0.05/1.32	181	7.13	100
610	CT610	9.0x610	0.35x24.0	175	79.40	0.09/2.29	177	6.97	100
812	CT812	9.0x812	0.35x32.0	175	79.40	0.09/2.29	177	6.97	100
1168	CT1168	9.0x1168	0.35x46.0	175	79.40	0.09/2.29	356	14.01	100