

**Notes:**

- Maximum Electrical Current: 

|     |    |    |  |  |
|-----|----|----|--|--|
| AWG | 16 | 14 |  |  |
| AMP | 18 | 30 |  |  |
- Maximum Electrical Rating: 150° 600 Volts
- Terminal Material: Copper
- Wire Range: 16-14 AWG (1.5-2.5mm<sup>2</sup>)
- Terminal Surface Treatment: Tin Plated
- #8 Stud Size
- Terminal Thickness: 0.80mm

**Standard (Metric)**

- 0.65" (16.5mm)
- 0.19" (4.8mm)
- 0.29" (7.4mm)
- 0.33" (8.5mm)
- 0.17" (4.3mm)
- 0.09" (2.3mm)
- 0.16" (4.1mm)

**Tolerances**

(Unless Otherwise Specified)

|                 |                              |              |      |
|-----------------|------------------------------|--------------|------|
| <b>CATEGORY</b> | Non Insulated Ring Terminals | <b>SCALE</b> | 4/1  |
| <b>PART #</b>   | RNBL2-4                      | <b>SHEET</b> | 1-2  |
| <b>MATERIAL</b> | Tin Plated Copper            | <b>PAGE</b>  | 10F2 |



FerrulesDirect

