



13' x 10' Flat Roof Insulated Cabin

The DuraMax Insulated Building is an energy efficient modular insulated building. The walls are manufactured with durable, coil coated galvanized steel that contains a fire-retardant CFC Free B2 Poly-Urethane insulation. This construction provides a strong, long lasting wall that reduces heat gain in summer or heat loss in winter.

These buildings are ideal for all weather conditions and can be used for various purposes, such as additional living space, an office, a hobby room, a secure storage space, or an equipment enclosure.

- Strong & Secure Cabin
- Metal Cladded Insulated Walls
- Will Not Rust, Rot, or Mildew
- Smooth Exterior and Interior Wall Finish
- Tall Walk-in Building (82 5/8" Tall)
- Wide 36 ¼" Door with Keyed Lock
- Corrugated Insulated Roof
- Can be Mounted Directly on a Concrete Floor
- Shelving can be Mounted Easily on All Wall Panels
- Easily Expandable on Either Left or Right Side
- Angular Roof Design with Rear Water Drainage System
- Industry's Longest 7 Year Limited Warranty

www.DuramaxBP.com

Building Products

FLAT ROOF INSULATED CABIN



Left Angle View





Front View



Right Angle View





With One Right Extension Kit Added

Roof Top View

Flat Ro	Flat Roof Insulated Cabin Dimensions							
Model No.	Approx. Size (Ft.)	Storage	Exterior Dimension (inches)			Interior Dimensions	Door Opening	Panel Color
30432	13' x 10'	129 Sq. Ft.		Base	Roof Edge to Edge	Wall to Wall		Off-White with
		887 Cu. Ft.	Width	159 ¼"	162 ¼"	156 7⁄8"	36 ¼"	Anthracite Trim
			Depth	120 5⁄8"	126 5∕ 8"	118 ¼"		
			Height		92"	82 5∕ 8"	82 ¾"	

Flat Roof Insulated Building One Extension Dimensions (Mountable on either Left or Right Side)							
Model No.	Approx. Size (Ft.)	Storage	Exterior Dimension (inches)			Interior Dimensions	Panel Color
34432	10' x 3.3'	32.29 Sq. Ft.		Base	Roof Edge to Edge	Wall to Wall	Off-White with
		223.5 Cu. Ft.	Width	39 1⁄2"	39 1⁄2"	39 ½"	Anthracite Trim
			Depth	120 5⁄8"	126 5⁄8"	118 ¼"	
			Height		92"	82 5⁄8"	

Packag	Packaging - Flat Roof Insulated Cabin						
SKU#	Pack	Contents	Package	Size (Inches)	Weight (Pounds)		
30432	1 of 2	Wall Panels, Door & 1 window	Wooden Frame	89" x 45" x 25"	743 lbs.		
30432	2 of 2	Roof Panels, Metal Profiles, Foundation & Accessories	Wooden Frame	124" x 46" x 11.5"	628 lbs.		
Packaging - Flat Roof Insulated Cabin One Extension Kit							
34432	1	Wall & Roof Panels, Metal Profiles	Wooden Frame	124" x 45" x 9"	407 lbs.		

The building is packaged in a heavy duty cardboard box, on a wooden frame. The packaging includes all components, hardware and an illustrated step-by-step instruction booklet. Shipped common carrier and requires lift gate for residential delivery.

Product Assembly

Approx. No. of Hrs Person Needed		Product			
6	2	Flat Roof Insulated Bldg			
9 2		Flat Roof Insulated Bldg with one Extension Kit			
Please refer to the Owner's Manual for more datail, available also at www.dwamayba.com					

Please refer to the Owner's Manual for more detail; available also at www.duramaxbp.com Need Help? Call 800-483-4674 or Email: support@uspolymersinc.com

CHECKLIST Prior to Building Purchase

- Check with your local city hall for building ordinances & CCR's.
- Be sure that intended placement of building is within your property lines.
- Do not construct building over utility lines (gas, electrical, water, telephone, cable, etc).
- Measure the size of the intended building site for ample space and make sure you have a level wooden or concrete foundation.



Rear Roof Rain Gutter System

FEATURES

Door Handle & Deadbolt Lock Included

Building Reinforced with Metal Columns

O -Panel Walls are Fire-retardant CFC Free Poly-Urethane Insulation.

Galvanized Metal Foundation Kit

One Window Kit Included

and Beams

