


Enhanced Climatisation for your well-being®









Barrisol® Clim®: the technical and practical benefits

It handles all the technical functions in one unit:

- Heating and cooling
- Area ventilation / Free cooling
- Acoustic and/or luminous membrane
- Option to integrate sound or projected video

Combining beauty and flexibility:

- No unsightly technical components on show
- Eliminates visible ventilation hardware.
 Frees up space on your walls and in your home
- Optimises the height of your plenum

Unparalleled comfort for enhanced well-being:

- Quiet
- Acoustic absorption
- A consistent temperature throughout
- A heightened system response time allows the unit to reach the desired temperature quickly
- No draught


Powerful and economical:

- Uses between 5 and 10% less energy than standard air-conditioning
- Environmentally friendly (less energy, less matter)
 AAA cold and AAA hot performance, according to the ISO 7730 standard
- Minimal maintenance required





Clim® Acoustics®









A15 NANOPERF® SINGLE-SHEET









Clim® Acoustic Light®



A15 NANOPERF® LUMINOUS DOUBLE-SHEET

NANOPERF® A15
characteristics
Holes: 500 000/m²
Hole diameter: ≈ 0,1 mm
Perforation rate: ≈ 1 %
Thickness: ≈ 0,18 mm
Reference: A15 + colour reference
















Barrisol® Clim®: An innovative design







With its unique and patented open shape, the Barrisol® Clim® can transfer air either by **blowing** (a) or by **suction** (b) between the plenum space and the rest of the room.


The **solid** version **©** of the unit allows you to prevent air passing through certain walls.







Barrisol® Clim®: for clean, healthy air and a constant temperature




- 1 Ambient air is taken in along the inner walls of the room, then channelled through a separating wall a, supported by the special Barrisol® Clim® unit.
- 2 The air enters the air conditioning unit*, where it is filtered and heated or cooled before being released into the plenum between the upper panel and the top of the Barrisol® Clim®.
- 3 A ventilation chamber can be connected to the system to inject new clean air into the plenum.
- 4 The conditioned air blends effectively with the new air and is distributed throughout the volume of the plenum.
- 5 The Barrisol® Clim® ceiling becomes one huge diffuser, radiating heat or coolness across the entire surface.
- 6 The conditioned air flows slowly over the outer walls.
 - * The Barrisol® Clim® system is compatible with all hotand cold-air production technologies which use forced air. Contact your approved Barrisol® installer for more information.






Barrisol® Clim®: Conditioning your air through the ceiling




- 1 Whether in summer or winter, conditioned air will flow gently over the outer walls. This eliminates any unpleasantly hot or cold walls.
- A natural flow of air develops throughout the space inside the room, at speeds so low they are barely perceptible.
- (3) Heat radiates through the entire surface of the ceiling, providing pleasant, gentle heat or coolness.

An example of the thermal distribution provided by the system

Cooling mode



Heating mode



Thanks to the consistent wall temperatures, the natural air flow and the large heat-exchanging surface of the ceiling, Barrisol® Clim® provides unparalleled comfort whether heating or cooling your home.


Occupants are surrounded by a gentle sensation of warmth or coolness. There is no noise and no air disturbance.

The ceiling works to radiate the heat or coolness extremely quickly. You'll feel a notable change in temperature within minutes.





Barrisol® Clim®: a breeze so gentle you'll hardly feel it



(1) with no risk of deforming the stretched sheet ceiling

(2) with no risk of condensation on the stretched sheet ceiling

Barrisol® Clim® evens out the temperature of both your walls and the air, wherever you are in the room.

The extremely low temperature difference between the head and the feet of an occupant (1.0°C in heating mode and 0.5°C in cooling mode), alongside the almost imperceptible air speed, means that Barrisol® Clim® can provide unparalleled comfort.

Unlike "static" air conditioning ceilings (which use hydraulic tubes), Barrisol[®] Clim[®] offers almost unlimited power.

The admissible power of 600W/m² while heating and 550W/m² while cooling ensures that it can meet your heating and cooling needs, wherever you are on the planet.





Acoustic luminous Climatisation

Our **Engineering Department** is at your service to study and carry out your project.

BARRISOL® NORMALU® S.A.S. Route du Sipes | 68680 Kembs | France

Tel.: +33 (0)3 89 83 20 20 - Fax: +33 (0)3 89 48 43 44 Email: mail@barrisol.com

www.barrisol.com



Living Heritage Company

Au cœur de l'innovation depuis 1967- At the heart of innovation since 1967





















