

## Modern and stylish design for private & public application

### Application



### Specifications

Aurora 7/11			
<b>General</b>	<b>Model Name</b>	Aurora 7	Aurora 11
<b>Power Input</b>	<b>Input Rating</b>	230Vac±10%, 45-65Hz, single-phase	400Vac±10%, 45-65Hz, three-phase
	<b>Number of Phase/Wire</b>	L+N+PE	L1+L2+L3+N+PE
	<b>Internal RCD</b>	DC 6mA + type A AC 30mA	DC 6mA + type A AC 30mA
<b>Power Output</b>	<b>Output Power</b>	7kW max.	11kW max.
	<b>Output Current</b>	32A max.	16A max.
	<b>Charging Interface</b>	Configuration1: IEC 62196-2 Type 2 tethered plug Configuration2: IEC 62196-2 Type 2 socket	
<b>User Interface &amp; Control</b>	<b>Status Indicators</b>	RGB LED	
	<b>Buttons and Switch</b>	Emergency stop button	
	<b>Card Reader</b>	ISO/IEC 14443 A/B Mifare RFID reader	
<b>Communication</b>	<b>Network Interface</b>	4G, Ethernet (optional), Wi-Fi (optional), Bluetooth (optional)	
	<b>Charging Protocol</b>	OCPP1.6J	
<b>Environmental</b>	<b>Operating Temperature</b>	-30°C - 50°C	
	<b>Storage Temperature</b>	-40°C- 70°C	
	<b>Humidity</b>	5% - 95% no condensation	
	<b>Altitude</b>	≤ 2000 m	
<b>Mechanical</b>	<b>Ingress Protection</b>	IP54(CaseB/Socket) / IP55(CaseC/Plug)	
	<b>Enclosure Protection</b>	IK10	
	<b>Cooling</b>	Natural cooling	
	<b>Dimension (WxHxD)</b>	282*409*148 mm	282*409*148 mm
	<b>Weight</b>	approx. 4.5kg	approx. 5.6kg
	<b>Connection</b>	Case B / Case C (5m Cable)	
	<b>Installation</b>	Wall-mounted, Column-mounted	
<b>Regulation</b>	<b>Certificate / Compliance</b>	CE	

Note: Pictures are for reference only, please prevail in kind.

+86 400 828 0768  
<http://www.starcharge.com>



## Compact design for public & semi-public scenarios

### Application



### Specifications

Saturn 22		
Power Input	<b>Input Rating</b>	400Vac±10%, 50/60Hz, three-phase
	<b>Number of Phase/Wire</b>	L1+L2+L3+N+PE
	<b>Internal RCD</b>	DC 6mA + type A AC 30mA
Power Output	<b>Output Power</b>	2 x 22kW max.
	<b>Output Current</b>	2 x 32A max.
	<b>Charging Interface</b>	Configuration1: IEC 62196-2 Type 2 tethered plug Configuration2: IEC 62196-2 Type 2 socket
User Interface & Control	<b>Status Indicators</b>	RGB LED
	<b>Buttons and Switch</b>	Emergency stop button (optional)
	<b>Card Reader</b>	ISO/IEC 14443 A/B Mifare RFID reader
Communication	<b>Network Interface</b>	4G, Ethernet (optional), Wi-Fi (optional), Bluetooth (optional)
	<b>Charging Protocol</b>	OCPP1.6J
Environmental	<b>Operating Temperature</b>	-30°C- 45°C (22+22kW Simultaneous Charging)
	<b>Storage Temperature</b>	-40°C- 70°C
	<b>Humidity</b>	5%-95% no condensation
	<b>Altitude</b>	≤ 3000 m
Mechanical	<b>Ingress Protection</b>	IP55
	<b>Enclosure Protection</b>	IK10 (Housing), IK8 (Screen)
	<b>Cooling</b>	Natural cooling
	<b>Dimension (WxHxD)</b>	395*504*197mm
	<b>Weight</b>	Approx. 15kg (CaseB) Approx.20kg (CaseC)
	<b>Charging Cable Length</b>	5m
	<b>Connection</b>	Case B, Case C
	<b>Installation</b>	Wall-mounted, Column-mounted
Regulation	<b>Certificate / Compliance</b>	CE

Note: Pictures are for reference only, please prevail in kind.

+86 400 828 0768  
<http://www.starcharge.com>

