RACKS BRAX®

COMPATIBILITY POCKET GUIDE





FAST DN! FAST DFF!

AWNING AND ACCESSORY MODELS

CLICK OR TAP ON AN AWNING/ACCESSORY BELOW TO TAKE YOU TO THE PAGE TO FIND OUT WHAT YOU NEED

OCAM® AWNING CROSS THREAD $2.0 \times 3.0 \text{m}$, $2.5 \times 3.0 \text{m}$, $3.0 \times 2.0 \text{m}$, $3.0 \times 2.5 \text{m}$,	0 x
3.0m	3
OCAM® CAR SIDE AWNING 1.4 x 2.0m, 1.4 x 2.5m	5
OCAM® PREMIUM WINGMAN 180 AWNING	6
OCAM® PREMIUM WINGMAN 270 XL AWNING	7
OCAM® PREMIUM WINGMAN AWNING (Driver/Passenger, also With Door model) 2.3m	
OCAM® PREMIUM WINGMAN DELUXE AWNING (Driver/Passenger) 2.3m	9
OCAM® QUALITY AWNING (Driver/Passenger) 2.75 x 1.75m	10
OCAM® WING AWNING (Driver/Passenger) 3.0 x 3.0m	11
OCAM® WING AWNING ROUND (Driver/Passenger) 2.5 x 2.5m	12
OCAM® WINGMAN AWNING TENT (Driver/Passenger) 2.3m	13
OCAM® WINGMAN DELUXE AWNING TENT (Driver/Passenger) 2.3m	14



OCAM® AWNING CROSS THREAD 2.0 x 3.0m. 2.5 x 3.0m. 3.0 x

2.0m, 3.0 x 2.5m, 3.0 x 3.0m

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

2 MOUNTING POINTS

HITCHES NEEDED 8159 - HD Hitch Standard*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

2 MOUNTING POINTS

SUPPLIED BRACKETS FROM OCAM® WILL WORK WITH THE HD HITCH **BRACKETS NEEDED**

RANGE.

✓ FOR BARS OR PLATFORM STYLES WITH 8300 - HD L50 L Brackets (DOUBLE)*; or (WITH NO PERIMETER LIP)

8304 - HD Adjustable Brackets Short (DOUBLE)*; or

FOR PLATFORM STYLES WITH UDINAL SLATS (WITH NO PERIMETER LIP)

8300 - HD L50 L Brackets (DOUBLE)*; or

8306 - HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO ROOF RACK GUIDE FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR **BENEFITS**

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 - HD Wall Mounts+

✓ LOCKED GARAGES ✓ WORKSHOP WALLS

UNSECURED LOCATION 8161 - HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

[†]NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.



OCAM® AWNING TENT 2.0 x 3.0m, 2.5 x 2.5m, 2.5 x 3.0m, 3.0 x 2.0m,

3.0 x 2.5m

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

2 MOUNTING POINTS

8159 - HD Hitch Standard* HITCHES NEEDED

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

2 MOUNTING POINTS

SUPPLIED BRACKETS FROM OCAM® WILL WORK WITH THE HD HITCH **BRACKETS NEEDED**

RANGE.

✓ FOR BARS OR PLATFORM STYLES WITH 8300 - HD L50 L Brackets (DOUBLE)*; or SLATS (WITH NO PERIMETER LIP)

8304 - HD Adjustable Brackets Short (DOUBLE)*; or

FOR PLATFORM STYLES WITH 8300 - HD L50 L Brackets (DOUBLE)*; or L SLATS (WITH NO PERIMETER LIP)

8306 - HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE PACKERS TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO ROOF RACK GUIDE FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR **BENEFITS**

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 - HD Wall Mounts+

✓ LOCKED GARAGES ✓ WORKSHOP WALLS

UNSECURED LOCATION 8161 - HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these



OCAM® CAR SIDE AWNING 1.4 x 2.0m, 1.4 x 2.5m

HITCHES REQUIRED MINIMUM FOR **FAST ON, FAST OFF!**

MOUNTING POINTS 2

HITCHES NEEDED 8159 – HD Hitch Standard*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS 2

BRACKETS NEEDED SUPPLIED BRACKETS FROM OCAM® WILL WORK WITH THE HD HITCH

RANGE.

✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP) 8300 - HD L50 L Brackets (DOUBLE)*; or

8304 - HD Adjustable Brackets Short (DOUBLE)*; or

✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)

8300 - HD L50 L Brackets (DOUBLE)*; or

8306 - HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE PACKERS TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO ROOF RACK GUIDE FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 - HD Wall Mounts⁺

✓ LOCKED GARAGES

✓ WORKSHOP WALLS

UNSECURED LOCATION 8161 – HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.



OCAM® PREMIUM WINGMAN 180 AWNING

HITCHES REQUIRED MINIMUM FOR **FAST ON, FAST OFF!**

MOUNTING POINTS 2

HITCHES NEEDED 8159 – HD Hitch Standard*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS 2

SUPPLIED BRACKETS FROM OCAM® REQUIRE 1 x 8.5MM HOLE TO BE BRACKETS NEEDED DRILLED PER BRACKET TO ACHIEVE 2 BRACKET HOLES AT 50MM

CENTRES.

✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP) 8300 – HD L50 L Brackets (DOUBLE)*; OR

8304 – HD Adjustable Brackets Short (DOUBLE)*; or

FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)

8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO ROOF RACK GUIDE FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 - HD Wall Mounts⁺

✓ LOCKED GARAGES
✓ WORKSHOP WALLS

UNSECURED LOCATION 8161 - HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

⁺NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.



OCAM® PREMIUM WINGMAN 270 XL AWNING

HITCHES REQUIRED MINIMUM FOR **FAST ON, FAST OFF!**

MOUNTING POINTS 3

HITCHES NEEDED 8182 – HD Hitch (TRIPLE)

ALSO WORKS WITH 8181

BRACKETS OPTIONAL

MOUNTING POINTS 3

SUPPLIED BRACKETS FROM OCAM® REQUIRE 1 x 8.5MM HOLE TO BE DRILLED PER BRACKET TO ACHIEVE 2 BRACKET HOLES AT 50MM

CENTRES.

FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP) 8301 – HD L50 L Brackets (TRIPLE)*; OR

8305 - HD Adjustable Brackets Short (TRIPLE)*; or

✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)

8307 – HD Adjustable Brackets Long (TRIPLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (*SOLD SEPARATEL* Y). REFER TO <u>ROOF RACK</u> <u>GUIDE</u> FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 - HD Wall Mounts*

✓ LOCKED GARAGES
✓ WORKSHOP WALLS

UNSECURED LOCATION 8161 - HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

 $^{ extstyle e$



OCAM® PREMIUM WINGMAN AWNING

(Driver/Passenger, also With Door model) 2.3m

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

3 MOUNTING POINTS

HITCHES NEEDED 8182 - HD Hitch (TRIPLE)

ALSO WORKS WITH 8181

BRACKETS OPTIONAL

(WITH NO PERIMETER LIP)

(WITH NO PERIMETER LIP)

3 MOUNTING POINTS

SUPPLIED BRACKETS FROM OCAM® REQUIRE 1 x 8.5MM HOLE TO BE **BRACKETS NEEDED** DRILLED PER BRACKET TO ACHIEVE 2 BRACKET HOLES AT 50MM

✓ FOR BARS OR PLATFORM STYLES WITH 8301 - HD L50 L Brackets (TRIPLE)*; or **E SLATS**

8305 - HD Adjustable Brackets Short (TRIPLE)*; or

FOR PLATFORM STYLES WITH 8307 - HD Adjustable Brackets Long (TRIPLE)*. **TUDINAL SLATS**

> *ROOF RACKS WITH PERIMETER LIPS REQUIRE PACKERS TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO ROOF RACK **GUIDE** FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 - HD Wall Mounts+

✓ LOCKED GARAGES ✓ WORKSHOP WALLS

UNSECURED LOCATION 8161 - HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these



OCAM® PREMIUM WINGMAN DELUXE AWNING

(Driver/Passenger) 2.3m

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

3 MOUNTING POINTS

HITCHES NEEDED 8182 - HD Hitch (TRIPLE)

ALSO WORKS WITH 8181

BRACKETS OPTIONAL

(WITH NO PERIMETER LIP)

(WITH NO PERIMETER LIP)

3 MOUNTING POINTS

SUPPLIED BRACKETS FROM OCAM® REQUIRE 1 x 8.5MM HOLE TO BE **BRACKETS NEEDED** DRILLED PER BRACKET TO ACHIEVE 2 BRACKET HOLES AT 50MM

✓ FOR BARS OR PLATFORM STYLES WITH 8301 - HD L50 L Brackets (TRIPLE)*; or **E SLATS**

8305 - HD Adjustable Brackets Short (TRIPLE)*; or

FOR PLATFORM STYLES WITH 8307 - HD Adjustable Brackets Long (TRIPLE)*. **TUDINAL SLATS**

> *ROOF RACKS WITH PERIMETER LIPS REQUIRE PACKERS TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO ROOF RACK **GUIDE** FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 - HD Wall Mounts+

✓ LOCKED GARAGES ✓ WORKSHOP WALLS

UNSECURED LOCATION 8161 - HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these



OCAM® QUALITY AWNING (Driver/Passenger) 2.75 x 1.75m

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

2 MOUNTING POINTS

8159 - HD Hitch Standard* HITCHES NEEDED

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

2 MOUNTING POINTS

SUPPLIED BRACKETS FROM OCAM® WILL WORK WITH THE HD HITCH **BRACKETS NEEDED**

RANGE.

✓ FOR BARS OR PLATFORM STYLES WITH 8300 - HD L50 L Brackets (DOUBLE)*; or SLATS (WITH NO PERIMETER LIP)

8304 - HD Adjustable Brackets Short (DOUBLE)*; or

FOR PLATFORM STYLES WITH L SLATS (WITH NO PERIMETER LIP)

8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO ROOF RACK GUIDE FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR **BENEFITS**

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 - HD Wall Mounts+

✓ LOCKED GARAGES ✓ WORKSHOP WALLS

UNSECURED LOCATION 8161 - HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle - these are for static wall use ONLY.



OCAM® WING AWNING (Driver/Passenger) 3.0 x 3.0m

HITCHES REQUIRED MINIMUM FOR **FAST ON, FAST OFF!**

MOUNTING POINTS 2

HITCHES NEEDED 8159 – HD Hitch Standard*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS 2

SUPPLIED BRACKETS FROM OCAM® REQUIRE 1 x 8.5MM HOLE TO BE BRACKETS NEEDED DRILLED PER BRACKET TO ACHIEVE 2 BRACKET HOLES AT 50MM

DRILLED PER BRACKET TO ACHIEVE 2 BRACKET HOLES AT SUMM

CENTRES.

✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS
(WITH NO PERIMETER LIP)

8300 – HD L50 L Brackets (DOUBLE)*; OR

8304 - HD Adjustable Brackets Short (DOUBLE)*; or

FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)

8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (*SOLD SEPARATEL* Y). REFER TO <u>ROOF RACK</u> <u>GUIDE</u> FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 – HD Wall Mounts⁺

✓ LOCKED GARAGES
✓ WORKSHOP WALLS

UNSECURED LOCATION 8161 – HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

RB-REF-014AE - OCAM Rev 0 (October 2023)



OCAM® WING AWNING ROUND (Driver/Passenger) 2.5 x 2.5m

HITCHES REQUIRED MINIMUM FOR **FAST ON, FAST OFF!**

MOUNTING POINTS 2

HITCHES NEEDED 8159 – HD Hitch Standard*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS 2

SUPPLIED BRACKETS FROM OCAM® REQUIRE 1 x 8.5MM HOLE TO BE BRACKETS NEEDED DRILLED PER BRACKET TO ACHIEVE 2 BRACKET HOLES AT 50MM

RILLED PER BRACKET TO ACHIEVE 2 BRACKET HOLES

CENTRES.

✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP) 8300 - HD L50 L Brackets (DOUBLE)*; or

8304 - HD Adjustable Brackets Short (DOUBLE)*; or

✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)

8306 - HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (*SOLD SEPARATEL* Y). REFER TO <u>ROOF RACK</u> <u>GUIDE</u> FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 - HD Wall Mounts⁺

✓ LOCKED GARAGES

✓ WORKSHOP WALLS

UNSECURED LOCATION 8161 – HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

⁺NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.



OCAM® WINGMAN AWNING TENT (Driver/Passenger) 2.3m

HITCHES REQUIRED MINIMUM FOR **FAST ON, FAST OFF!**

2 MOUNTING POINTS

8159 - HD Hitch Standard* HITCHES NEEDED

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

2 MOUNTING POINTS

SUPPLIED BRACKETS FROM OCAM® REQUIRE 1 x 8.5MM HOLE TO BE **BRACKETS NEEDED** DRILLED PER BRACKET TO ACHIEVE 2 BRACKET HOLES AT 50MM

CENTRES.

✓ FOR BARS OR PLATFORM STYLES WITH 8300 - HD L50 L Brackets (DOUBLE)*; or SLATS (WITH NO PERIMETER LIP)

8304 - HD Adjustable Brackets Short (DOUBLE)*; or

FOR PLATFORM STYLES WITH L SLATS (WITH NO PERIMETER LIP)

8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO ROOF RACK GUIDE FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 - HD Wall Mounts+

✓ LOCKED GARAGES

✓ WORKSHOP WALLS

UNSECURED LOCATION 8161 - HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle - these are for static wall use ONLY.

RB-REF-014AE - OCAM Rev 0 (October 2023)



OCAM® WINGMAN DELUXE AWNING TENT

(Driver/Passenger) 2.3m

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS 3

HITCHES NEEDED 8182 – HD Hitch (TRIPLE)

ALSO WORKS WITH 8181

BRACKETS OPTIONAL

(WITH NO PERIMETER LIP)

MOUNTING POINTS 3

SUPPLIED BRACKETS FROM OCAM® REQUIRE 1 x 8.5MM HOLE TO BE BRACKETS NEEDED DRILLED PER BRACKET TO ACHIEVE 2 BRACKET HOLES AT 50MM

CENTRES

✓ FOR BARS OR PLATFORM STYLES WITH 8301 – HD L50 L Brackets (TRIPLE)*; OR

8305 - HD Adjustable Brackets Short (TRIPLE)*; or

FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP) 8307 – HD Adjustable Brackets Long (TRIPLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO ROOF RACK GUIDE FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR

VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.

SECURED LOCATION 8160 - HD Wall Mounts⁺

✓ LOCKED GARAGES
✓ WORKSHOP WALLS

UNSECURED LOCATION 8161 - HD Lockable Wall Mounts⁺

✓ OPEN CARPORTS

✓ PUBLIC/SHARED GARAGE AREA

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

RB-REF-014AE - OCAM Rev 0 (October 2023)