

RACKS BRAX.®

COMPATIBILITY POCKET GUIDE

FOR

IRONMAN 4X4

*FAST ON!
FAST OFF!*

AWNING AND ACCESSORY MODELS

CLICK OR TAP ON AN AWNING/ACCESSORY BELOW
TO TAKE YOU TO THE PAGE TO FIND OUT WHAT YOU NEED

IRONMAN® DELTAWING 270 XT-71..... 3
IRONMAN® DELTAWING 270 XTR-71..... 4
IRONMAN® DELTAWING 270 XTR-143..... 5
IRONMAN® INSTANT ENSUITE 1.1m, 1.4m, 2m, 2.5m 6



IRONMAN® DELTAWING 270 XT-71

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	9000 – XD Hitch (DOUBLE)*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	SUPPLIED BRACKETS FROM IRONMAN 4X4® WILL WORK WITH THE XD HITCH RANGE.
<ul style="list-style-type: none"> ✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP) 	9100 – XD Adjustable Brackets Short (DOUBLE)*; OR 9104 – XD Side Twist Bracket Short Foot (DOUBLE)*.
<ul style="list-style-type: none"> ✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP) 	9102 – XD Adjustable Brackets Long (DOUBLE)*; OR 9106 – XD Side Twist Bracket Long Foot (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION <ul style="list-style-type: none"> ✓ LOCKED GARAGES ✓ WORKSHOP WALLS 	9010 – XD Wall Mounts ⁺
UNSECURED LOCATION <ul style="list-style-type: none"> ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA 	9011 – XD Lockable Wall Mounts ⁺

⁺NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

IRONMAN® DELTAWING 270 XTR-71

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	9000 – XD Hitch (DOUBLE)*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	SUPPLIED BRACKETS FROM IRONMAN 4X4® WILL WORK WITH THE XD HITCH RANGE.
<ul style="list-style-type: none"> ✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP) 	9100 – XD Adjustable Brackets Short (DOUBLE)*; OR 9104 – XD Side Twist Bracket Short Foot (DOUBLE)*.
<ul style="list-style-type: none"> ✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP) 	9102 – XD Adjustable Brackets Long (DOUBLE)*; OR 9106 – XD Side Twist Bracket Long Foot (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION <ul style="list-style-type: none"> ✓ LOCKED GARAGES ✓ WORKSHOP WALLS 	9010 – XD Wall Mounts ⁺
UNSECURED LOCATION <ul style="list-style-type: none"> ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA 	9011 – XD Lockable Wall Mounts ⁺

⁺NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

IRONMAN® DELTAWING 270 XTR-143

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	9000 – XD Hitch (DOUBLE)*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	SUPPLIED BRACKETS FROM IRONMAN 4X4® WILL WORK WITH THE XD HITCH RANGE.
<ul style="list-style-type: none"> ✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP) 	9100 – XD Adjustable Brackets Short (DOUBLE)*; OR 9104 – XD Side Twist Bracket Short Foot (DOUBLE)*.
<ul style="list-style-type: none"> ✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP) 	9102 – XD Adjustable Brackets Long (DOUBLE)*; OR 9106 – XD Side Twist Bracket Long Foot (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION <ul style="list-style-type: none"> ✓ LOCKED GARAGES ✓ WORKSHOP WALLS 	9010 – XD Wall Mounts ⁺
UNSECURED LOCATION <ul style="list-style-type: none"> ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA 	9011 – XD Lockable Wall Mounts ⁺

⁺NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

IRONMAN® INSTANT ENSUITE 1.1m, 1.4m, 2m, 2.5m

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard*
ALSO WORKS WITH	8162*, 8180*

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	SUPPLIED BRACKETS FROM IRONMAN 4X4® WILL WORK WITH THE HD HITCH RANGE.
<ul style="list-style-type: none"> ✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP) 	8300 – HD L50 L Brackets (DOUBLE)*; OR 8304 – HD Adjustable Brackets Short (DOUBLE)*; OR
<ul style="list-style-type: none"> ✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP) 	8300 – HD L50 L Brackets (DOUBLE)*; OR 8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION <ul style="list-style-type: none"> ✓ LOCKED GARAGES ✓ WORKSHOP WALLS 	8160 – HD Wall Mounts ⁺
UNSECURED LOCATION <ul style="list-style-type: none"> ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA 	8161 – HD Lockable Wall Mounts ⁺

⁺NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.