



15" SIGNATURE SERIES
Beverage Dispenser - Draft Arm Tower



eco friendly
R600a Refrigerant



JOB	
AREA	
ITEM NO.	
MODEL NO.	



Solid Door Model



650SS Forward Sealing Flow Control Beer Faucet

MODELS	DESCRIPTION
HP15TS-4-1L/R-1	Indoor Signature Series Beverage Dispenser Solid Stainless Steel Door 1 Faucet
HP15TS-4-2L/R-1	Indoor Signature Series Beverage Dispenser Solid Panel Ready Door 1 Faucet
HP15TO-4-1L/R-1	Outdoor Signature Series Beverage Dispenser Solid Stainless Steel Door 1 Faucet
HP15TO-4-2L/R-1	Outdoor Signature Series Beverage Dispenser Solid Panel Ready Door 1 Faucet
HP15TM-4-1L/R-1	Marine Signature Series Beverage Dispenser Solid Stainless Steel Door 1 Faucet
HP15TM-4-2L/R-1	Marine Signature Series Beverage Dispenser Solid Panel Ready Door 1 Faucet

KEY PRODUCT FEATURES AND BENEFITS

- 1000 BTU/hr capacity delivers industry's most energy efficient cool down; indoors or outdoors
- Up to 70% faster cooling speeds than leading competitor
- Variable speed compressor minimizes sound; up to 30% quieter than competitors
- Commercial-grade all stainless steel interior and exterior provide superior durability and easy cleaning
- Perlick Anti-Condensation System™ eliminates condensation from forming on the cabinet (Outdoor and Marine models only)
- Marine & Coastal Grade with Perlick Armor™ upgrades stainless steel, fasteners, and refrigeration system to the highest blend of corrosion resistance and food safety

Quick Features:

- Forced air refrigeration technology ensures consistent temperature throughout entire keg maintaining flavor better than other brands
- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready doors to match your design style
- Audible door alarm warns user if door is held open
- White LED task lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero ozone depletion potential
- Accommodates one (1) 1/6 barrel



One 1/6 barrel



15" SIGNATURE SERIES
Beverage Dispenser - Draft Arm Tower

MODEL NUMBERS		HP15TS	HP15TO	HP15TM
MODEL DESCRIPTION		15" Indoor Beverage Dispenser - Draft Arm Tower	15" Outdoor Beverage Dispenser - Draft Arm Tower	15" Marine Beverage Dispenser - Draft Arm Tower
ATTRIBUTES				
Perlick Anti-Condensation System		NO	YES	YES
Perlick Armor™		NO	NO	YES
OVERALL DIMENSIONS	Width - in. (mm)	14-7/8" (378 mm.)	14-7/8" (378 mm.)	14-7/8" (378 mm.)
	Depth - in. (mm)	24" (610 mm.)	24" (610 mm.)	24" (610 mm.)
	Height - in. (mm)	34-1/4" (870 mm.)	34-1/4" (870 mm.)	34-1/4" (870 mm.)
STANDARD OPENING DIMENSIONS	Width - in. (mm)	15" (381 mm.)	15" (381 mm.)	15" (381 mm.)
	Depth - in. (mm)	24-7/8" (632 mm.)	24-7/8" (632 mm.)	24-7/8" (632 mm.)
	Height - in. (mm)	34-1/2" (876 mm.)	34-1/2" (876 mm.)	34-1/2" (876 mm.)
INTERNAL VOLUME Net. Cu. Ft.		2.8 cu. ft.	2.8 cu. ft.	2.8 cu. ft.
SHIPPING WEIGHT Lbs. (kg.)		144 lbs (100.7 kg.)	144 lbs (100.7 kg.)	144 lbs (100.7 kg.)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph	115 VAC/60 Hz/1 Ph	115 VAC/60 Hz/1 Ph
	Running Load Amps	1.7 amps	1.7 amps	1.7 amps
	Electrical Connection	Cord connected	Cord connected	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P	NEMA 3 Prong 5-15P	NEMA 3 Prong 5-15P
	Cord Length	6'	6'	6'
	Defrost Initiation	Automatic	Automatic	Automatic
	Defrost Type	Off cycle	Off cycle	Off cycle
	Thermostat	Digital	Digital	Digital
	Lighting Type	LED	LED	LED
REFRIGERATION SPECIFICATIONS	Refrigerant	R600a (44g)	R600a (44g)	R600a (44g)
	Expansion Device	Capillary Tube	Capillary Tube	Capillary Tube
	Temperature Settings F°(C°)	33° (0.5°) - 48° (8.8°) Factory Set Point 36° (2.2°)	33° (0.5°) - 48° (8.8°) Factory Set Point 36° (2.2°)	33° (0.5°) - 48° (8.8°) Factory Set Point 36° (2.2°)
	Heat Rejection (at 75°F)	300 BTU/hr	300 BTU/hr	300 BTU/hr
	Pull Down Capacity	1000 BTU/hr	1000 BTU/hr	1000 BTU/hr
	Front Vented	Yes	Yes	Yes
PLUMBING		None Required	None Required	None Required

Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.

ACCESSORIES

MODEL NOS.	DESCRIPTION
(L)	Factory Installed Lock
66736-15	Caster Kit for HP15 models
63797	Beer Dispenser Cleaning Kit
400305	Keg Coupler, Lo-Boy "S" Series
67141-1	Perlick Faucet Handle
BLC4/32	Beer Dispenser Sanitizer (4oz. or 32 oz.)

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit perlick.com.



15" SIGNATURE SERIES
Beverage Dispenser - Draft Arm Tower

	CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
INDOOR	HP15TS-4-1L-1	HP15TS4C-B0-SLF0T	Left	No
	HP15TS-4-1R-1	HP15TS4C-B0-SRF0T	Right	No
	HP15TS-4-2L-1	HP15TS4C-B0-PL00T	Left	No
	HP15TS-4-2R-1	HP15TS4C-B0-PR00T	Right	No
	HP15TS-4-1LL-1	HP15TS4C-B0-SLFLT	Left	Yes
	HP15TS-4-1RL-1	HP15TS4C-B0-SRFLT	Right	Yes
	HP15TS-4-2LL-1	HP15TS4C-B0-PLOLT	Left	Yes
	HP15TS-4-2RL-1	HP15TS4C-B0-PROLT	Right	Yes
OUTDOOR	HP15TO-4-1L-1	HP15TO4C-B0-SLF0T	Left	No
	HP15TO-4-1R-1	HP15TO4C-B0-SRF0T	Right	No
	HP15TO-4-2L-1	HP15TO4C-B0-PL00T	Left	No
	HP15TO-4-2R-1	HP15TO4C-B0-PR00T	Right	No
	HP15TO-4-1LL-1	HP15TO4C-B0-SLFLT	Left	Yes
	HP15TO-4-1RL-1	HP15TO4C-B0-SRFLT	Right	Yes
	HP15TO-4-2LL-1	HP15TO4C-B0-PLOLT	Left	Yes
	HP15TO-4-2RL-1	HP15TO4C-B0-PROLT	Right	Yes
MARINE & COASTAL	HP15TM-4-1L-1	HP15TM4C-B0-MLF0T	Left	No
	HP15TM-4-1R-1	HP15TM4C-B0-MRF0T	Right	No
	HP15TM-4-2L-1	HP15TM4C-B0-PL00T	Left	No
	HP15TM-4-2R-1	HP15TM4C-B0-PR00T	Right	No
	HP15TM-4-1LL-1	HP15TM4C-B0-MLFLT	Left	Yes
	HP15TM-4-1RL-1	HP15TM4C-B0-MRFLT	Right	Yes
	HP15TM-4-2LL-1	HP15TM4C-B0-PLOLT	Left	Yes
	HP15TM-4-2RL-1	HP15TM4C-B0-PROLT	Right	Yes



15" SIGNATURE SERIES
Beverage Dispenser - Draft Arm Tower

