# Perimeter Series Range Hoods EMS9026 Spec Sheet



FOTILE EMS9026 Perimeter Vent Range hood is powerful and has a modern canopy design. Wall mountable, this certified Range Hood offers superior smoke, grease, and odor extraction. With its Patented 2.0 Generation Capture Shield that can be manually adjusted, the range hood actively responds to surrounding smoke for effective ventilation. It is also exceptionally quiet so you can have a casual conversation as you are preparing a meal. Available in Stainless Steel.





### Key Features



Adjusting Capture Shield Technology to accurately absorb, and extract smoke and grease



Auto Turbo Mode for Quick Extra Power



97% Odor Reduction Rate &92.5% Grease Separation Rate



Covers 7.2 ft <sup>2</sup> of Cooking Area (5-6 Burners)

## Secondary Features

Auto Delay Shutoff
 Extracts Lingering Odors After You Are

Powerful LED Light

Lights Up Your Cooktop

**Done Cooking** 

Large Oil Collection Cup
 Detachable and Easy to Clean

Detachable Capture Shield

Easy to Clean

# Perimeter Series Range Hoods EMS9026 Spec Sheet



### Specifications Table

| Model                         | EMS9026                           |
|-------------------------------|-----------------------------------|
| Certification                 | ETL                               |
| Width(inch)                   | 35 5/16                           |
| Installation                  | Wall Mount                        |
| Speed Setting                 | 2+Turbo                           |
| Max. EQUIV.CFM                | 1000*                             |
| Max Static Pressure(Pa)       | 500                               |
| Power Supply(V/Hz)            | 120/60                            |
| Noise Level(dB)               | 43.79 / 49.83 / 56.06             |
| Illumination(W)               | 2W (LED)                          |
| Motor                         | AC Motor                          |
| Operation Type                | Touch                             |
| Delay Shutoff                 | 2min                              |
| Capture Shield                | Manually-Adjustable               |
| Screen Lock                   | N                                 |
| <b>Grease Filtration Rate</b> | 92.5%                             |
| Odor Reduction Rate           | 97%                               |
| Warranty                      | Labor: 2 Years                    |
|                               | Parts: 5 Years(Limited)           |
|                               | Motors: Lifetime Limited Warranty |

\*FOTILE Equivalent CFM is a higher CFM rating due to our filterless technology that combines WhisPower Motors and Capture-Shield design. By utilizing this technology, **FOTILE** applies the Coanda Effect by accelerating smoke extraction and grease separation, and increasing our Capture Efficiency. This enables FOTILE to cover a larger cooktop surface (7.2 Sq Ft) and achieve a 92.5% oil filtration rate, and 97% odor reduction rate, keeping your kitchen smoke free and smelling fresh.

#### Installation Dimensions

#### 

# Installation Examples



