

24" SIGNATURE SERIES DUAL-ZONE Freezer/Refrigerator Drawers







JOB	
AREA	
ITEM NO.	
MODEL NO.	



Drawer Model

MODELS	DESCRIPTION
HP24ZS-4-5	Indoor Signature Series Dual Zone Refrigerator & Freezer Stainless Steel Drawers
HP24ZS-4-6	Indoor Signature Series Dual Zone Refrigerator & Freezer Panel Ready Drawers
HP24ZO-4-5	Outdoor Signature Series Dual Zone Refrigerator & Freezer Stainless Steel Drawers
HP24ZO-4-6	Outdoor Signature Series Dual Zone Refrigerator & Freezer Panel Ready Drawers
HP24ZM-4-5	Marine Signature Series Dual Zone Refrigerator & Freezer Stainless Steel Drawers
HP24ZM-4-6	Marine Signature Series Dual Zone Refrigerator & Freezer Panel Ready Drawers

KEY PRODUCT FEATURES AND BENEFITS

- Patented dual zone technology store fresh and frozen foods at their appropriate temperatures independently controlled zones can be set to properly store variety of fresh and frozen foods or beverages
- 1000 BTU/hr capacity delivers industry's most energy efficient cool down, indoors or outdoors
- Variable speed compressor minimizes sound, up to 30% quieter than competitive brands
- · Commercial-grade all stainless steel interior and exterior provides superior durability and easy cleaning
- Perlick Anti-Condensation System[™] eliminates condensation from forming on the cabinet (Outdoor and Marine models only)
- Marine & Coastal Grade with Perlick Armor™ upgrades stainless steel, fasteners, and refrigeration system to the highest blend of corrosion resistance and food safety

Quick Features:

- Smooth glide self-closing drawers offer high storage capacity
- NSF Rated drawer pans available to keep fresh cut ingredients ready for quick access in food grade commercial drawer pans
- Industry's best full 6 year warranty for owner ease of mind
- All models available with stainless steel or panel ready door to match your design style
- Audible door alarm warns user if door is left open
- White LED task lighting illuminates cabinet when drawers are opened
- R600a Natural Refrigerant maximum energy efficiency with zero global warming impact



24" SIGNATURE SERIES DUAL-ZONE Freezer/Refrigerator Drawers

Freezer Drawers Freezer Drawers Freezer Drawers Freezer Drawers Freezer Drawers	MODEL NUMBERS		HP24ZS	HP24ZO	HP24ZM	
NO YES YES	MODEL DESCRIPTION					
NO NO YES	ATTRIBUTES					
Width - in. (mm) 23-7/8" (606 mm.) 24" (610 mm.) 34-1/4" (870 mm.) 24" (610 mm.) 24-7/8" (632 mm.) 24-7/8" (632 mm.) 34-1/2" (876 mm.) 34-1/2" (Perlick Anti-Condensation System		NO	YES	YES	
Depth - in. (mm) 24" (610 mm.) 34-1/4" (870 mm.) 24" (610 mm.) 24-7/8" (632 mm.) 24-7/8" (632 mm.) 24-7/8" (632 mm.) 24-7/8" (632 mm.) 34-1/2" (876 mm.) 34-1/	Perlick Armor™		NO	NO	YES	
Height - in. (mm) 34-1/4" (870 mm.) 24" (610 mm.) 24-7/8" (632 mm.) 24-7/8" (632 mm.) 24-7/8" (632 mm.) 24-7/8" (632 mm.) 34-1/2" (876 mm.) 34-1		Width - in. (mm)	23-7/8" (606 mm.)	23-7/8" (606 mm.)	23-7/8" (606 mm.)	
Width - in. (mm) 24" (610 mm.) 24-7/8" (632 mm.) 34-1/2" (876 mm.)	OVERALL DIMENSIONS	Depth - in. (mm)	24" (610 mm.)	24" (610 mm.)	24" (610 mm.)	
Depth - in. (mm) 24-7/8" (632 mm.) 34-1/2" (876 mm.) 34-1/		Height - in. (mm)	34-1/4" (870 mm.)	34-1/4" (870 mm.)	34-1/4" (870 mm.)	
Height - in. (mm) 34-1/2" (876 mm.) 34-1		Width - in. (mm)	24" (610 mm.)	24" (610 mm.)	24" (610 mm.)	
TITERNAL VOLUME Net. Cu. Ft. 5.0 cu. ft.	OPENING DIMENSIONS	Depth - in. (mm)	24-7/8" (632 mm.)	24-7/8" (632 mm.)	24-7/8" (632 mm.)	
HIPPING WEIGHT Lbs. (kg.)		Height - in. (mm)	34-1/2" (876 mm.)	34-1/2" (876 mm.)	34-1/2" (876 mm.)	
Electrical Supply 115 VAC/60 Hz/1 Ph 115 VAC	INTERNAL VOLUME Net. Cu. Ft.		5.0 cu. ft.	5.0 cu. ft.	5.0 cu. ft.	
Running Load Amps 2.2 amps 2.2 amps 2.2 amps Electrical Connection Cord connected Cord connected Cord connected Cord Plug Type NEMA 3 Prong 5-15P NEMA 3 Prong 5-15P Cord Length 6' 6' 6' Defrost Initiation Time Time Time Defrost Type Hot Gas Hot Gas Hot Gas Thermostat Digital Digital Digital Lighting Type LED LED LED Refrigerant R600a (57g) R600a (57g)	SHIPPING WEIGHT Lbs. (kg.)		144 lbs (100.7 kg.)	144 lbs (100.7 kg.)	144 lbs (100.7 kg.)	
Electrical Connection Cord connected Cord connected Cord connected Cord Plug Type NEMA 3 Prong 5-15P NEMA 3 Prong 5-15P NEMA 3 Prong 5-15P Cord Length 6' 6' 6' Defrost Initiation Time Time Time Defrost Type Hot Gas Hot Gas Hot Gas Thermostat Digital Digital Digital Lighting Type LED LED LED Refrigerant R600a (57g) R600a (57g)	ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph	115 VAC/60 Hz/1 Ph	115 VAC/60 Hz/1 Ph	
Cord Plug Type NEMA 3 Prong 5-15P NEMA 3 Pro		Running Load Amps	2.2 amps	2.2 amps	2.2 amps	
Cord Length 6' 6' 6' Defrost Initiation Time Time Time Defrost Type Hot Gas Hot Gas Hot Gas Thermostat Digital Digital Digital Lighting Type LED LED LED Refrigerant R600a (57g) R600a (57g) R600a (57g)		Electrical Connection	Cord connected	Cord connected	Cord connected	
Defrost Initiation Time Time Time Defrost Type Hot Gas Hot Gas Hot Gas Thermostat Digital Digital Digital Lighting Type LED LED LED Refrigerant R600a (57g) R600a (57g) R600a (57g)		Cord Plug Type	NEMA 3 Prong 5-15P	NEMA 3 Prong 5-15P	NEMA 3 Prong 5-15P	
Defrost Type Hot Gas Hot Gas Hot Gas Thermostat Digital Digital Digital Lighting Type LED LED LED Refrigerant R600a (57g) R600a (57g) R600a (57g)		Cord Length	6′	6′	6′	
Thermostat Digital Digital Digital Lighting Type LED LED LED Refrigerant R600a (57g) R600a (57g) R600a (57g)		Defrost Initiation	Time	Time	Time	
Lighting Type LED LED LED Refrigerant R600a (57g) R600a (57g) R600a (57g)		Defrost Type	Hot Gas	Hot Gas	Hot Gas	
Refrigerant R600a (57g) R600a (57g) R600a (57g)		Thermostat	Digital	Digital	Digital	
		Lighting Type	LED	LED	LED	
Expansion Device Capillary Tube Capillary Tube Capillary Tube		Refrigerant	R600a (57g)	R600a (57g)	R600a (57g)	
	REFRIGERATION SPECIFICATIONS	Expansion Device	Capillary Tube	Capillary Tube	Capillary Tube	
Temperature Settings F°(C°) -10° (-23.3°) - 10° (-12.2°) -10° (-23.3°) - 10° (-23.3°) - 10° (-12.2°) -10° (-23.3°) - 10° (-12.2°) -10° (-23.3°) - 10° (-12.2°) -10° (-23.3°) - 10° (-12.2°) -10° (-23.3°) - 10° (-12.2°) -10° (-23.3°) - 10° (-12.2°) -10° (-12.2°)		Temperature Settings F°(C°)	, , , ,	. , , , , ,	. , , , , ,	
Heat Rejection (at 75°F) 700 BTU/hr 700 BTU/hr 700 BTU/hr		Heat Rejection (at 75°F)	700 BTU/hr	700 BTU/hr	700 BTU/hr	
Pull Down Capacity 1000 BTU/hr 1000 BTU/hr 1000 BTU/hr		Pull Down Capacity	1000 BTU/hr	1000 BTU/hr	1000 BTU/hr	
Front Vented Yes Yes Yes		Front Vented	Yes	Yes	Yes	
LUMBING None Required None Required None Required	PLUMBING		None Required	None Required	None Required	

Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.

ACCESSORIES


MODEL NOS.	DESCRIPTION
(DL)	Add DL to end of model number
RS-SK-24L/R	Stacking Kit for HP24/HC24/HA24 models
66736	Caster Kit for HP24/HC24/HA24 models
RK24DP	Drawer Pan Tray (3 SS pans with covers)


Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit **perlick.com.**




24" SIGNATURE SERIES DUAL-ZONE Freezer/Refrigerator Drawers

	CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Door Type	Hinge Side	Lock
INDOOR	HP24ZS-4-5	HP24ZS4G-00-EDF0D	Drawers Stainless Steel	Drawers	No
	HP24ZS-4-6	HP24ZS4G-00-DD00D	Drawers Panel Ready	Drawers	No
Ž	HP24ZS-4-5DL	HP24ZS4G-00-EDFLD	Drawers Stainless Steel	Drawers	Yes
	HP24ZS-4-6DL	HP24ZS4G-00-DD0LD	Drawers Panel Ready	Drawers	Yes
œ	HP24ZO-4-5	HP24ZO4G-00-EDF0D	Drawers Stainless Steel	Drawers	No
OUTDOOR	HP24ZO-4-6	HP24ZO4G-00-DD00D	Drawers Panel Ready	Drawers	No
	HP24ZO-4-5DL	HP24ZO4G-00-EDFLD	Drawers Stainless Steel	Drawers	Yes
	HP24ZO-4-6DL	HP24ZO4G-00-DD0LD	Drawers Panel Ready	Drawers	Yes
⊗ ⊣	HP24ZM-4-5	HP24ZM4G-00-QDF0D	Drawers Stainless Steel	Drawers	No
MARINE &	HP24ZM-4-6	HP24ZM4G-00-DD00D	Drawers Panel Ready	Drawers	No
	HP24ZM-4-5DL	HP24ZM4G-00-QDFLD	Drawers Stainless Steel	Drawers	Yes
	HP24ZM-4-6DL	HP24ZM4G-00-DD0LD	Drawers Panel Ready	Drawers	Yes







Form No. Z2770 Rev 02.02.2022