

Central Ducted DC INVERTER HEAT PUMP



Introducing an affordable multi-position air handler with a worry-free warranty.

Version Date: 08-16-22

The comfort you crave & the savings you expect.

Reliable, year-round heating and cooling in any home with the MRCOOL® Central Ducted Air Handler and Condenser.



As homeowners think about the functionality of their HVAC system, MRCOOL® is ready to provide flexible comfort upgrade solutions like never before.

The MRCOOL® Central Ducted series offers something for everyone: an advanced yet affordable system; an easy-to-install system that can adapt to most installation conditions and changing demands; an energy-efficient system that doesn't compromise on comfort.

With a 10-year parts and labor warranty*, you can trust in this MRCOOL® Ducted Air Handler and Condenser to bring you the comfort you crave while saving you money.



Multi-Position Installation

This quiet, compact unit can be installed with an UPFLOW, DOWNFLOW, HORIZONTAL LEFT or HORIZONTAL RIGHT configuration. This means that it can essentially meet any ductwork requirements you may have, making it the perfect fit for any application.



Features and Benefits


- Up to 22 SEER and 11 HSPF
- Variable Speed
- R-410A Refrigerant
- Painted Galvanized Steel
- Quiet Operation

- Compact, Side Discharge Design
- Multi-Position Installation
- Slide-Out Blower
- Wired Thermostat Included
- Follow Me[™] Function

- Easy-Access Removable Filter
- Modular Design
- Self-Diagnostics
- Easy Maintenance









Line Sets & Coupler Kits

The Central Ducted 18K, 24K, and 30K condensers come with a 25-foot DIY® Quick Connect® line set included.

The 36K, 48K, and 60K condensers do not come standard with a Quick Connect line set, but are compatible with the optional No Vac® Quick Connect® Line Sets and coupler kits.

Choose absolute comfort... the Central Ducted Air Handler and Condenser from MRCOOL.



| MODEL NO. CONDENSER MODEL NO. | | Unit | CENTRAL-18-HP-MUAH-230-25 CENTRAL-18-HP-C-230-25 | CENTRAL-24-HP-MUAH-230-25 CENTRAL-24-HP-C-230-25 | CENTRAL-30-HP-MUAH-230-25 CENTRAL-30-HP-C-230-25 | CENTRAL-36-HP-MUAH-230-00 CENTRAL-36-HP-C-230-00** | CENTRAL-48-HP-MUAH-230-00 CENTRAL-48-HP-C-230-00** | CENTRAL-60-HP-MUAH-230- CENTRAL-60-HP-C-230-00* |
|----------------------------------|-------------------|---------|---|---|---|---|---|--|
| CAPACITY 8 | & PERFORMANCE | | | | | | | |
| Cooling | Capacity | Btu/h | 18000 | 24000 | 30000 | 36000 | 47000 | 57000 |
| | SEER | Btu/w | 22 | 19.2 | 18.5 | 18 | 17.3 | 18 |
| | EER | Btu/w | 12.5 | 12.5 | 10.3 | 10.4 | 9.3 | 10.3 |
| Heating | Capacity | Btu/h | 18000 | 24000 | 30000 | 36000 | 55000 | 60000 |
| | HSPF4 | Btu/w | 11 | 10 | 9.5 | 9.1 | 10 | 9.2 |
| | HSPF5 | Btu/w | 9 | 8.5 | 8 | 7.1 | 8.2 | 7.6 |
| Indoor Noise Level (Hi/Mi/Lo) | | dB(A) | 39.5/38.5/35.5 | 43.0/41.5/38.0 | 46.5/43/39.5 | 46.8/44/41.3 | 53/50/46 | 52.5/49/44 |
| Outdoor Noise Level | | dB(A) | 57 | 58 | 63 | 61 | 59 | 61 |
| ELECTRICA | L PARTS | | | | | | | |
| Power Supp | ly (Indoor) | V~Hz.ph | N/A | N/A | N/A | 208/230v~60Hz,1ph | 208/230v~60Hz,1ph | 208/230v~60Hz,1pt |
| Power Supp | ly (Outdoor) | V~Hz.ph | 208/230v~60Hz,1ph | 208/230v~60Hz,1ph | 208/230v~60Hz,1ph | 208/230v~60Hz,1ph | 208/230v~60Hz,1ph | 208/230v~60Hz,1ph |
| Min Circuit | Ampacity (Indoor) | Α | 2.5 | 4 | 4.5 | 5 | 7.5 | 9 |
| Max Fuse (Indoor) | | Α | 15 | 15 | 15 | 15 | 15 | 15 |
| Min Circuit Ampacity (Outdoor) | | Α | 18 | 22 | 25 | 24 | 34 | 34 |
| Max Fuse (Outdoor) | | A | 30 | 35 | 40 | 40 | 50 | 60 |
| DIMENDION | IO & WEIGHT | | | | | <u>:</u> | 1 | |
| | IS & WEIGHT | in a la | 01.0017.5045.00 | 01.0017.5045.00 | 01 00 01 00 40 00 | 01 00 01 00 40 00 | 01 00 01 00 40 00 | 01 00 04 40 50 00 |
| Indoor Unit | Dimension (WxDxH) | inch | 21.02 x 17.52 x 45.00 | 21.02 x 17.52 x 45.00 | 21.02 x 21.02 x 49.02 | 21.02 x 21.02 x 49.02 | 21.02 x 21.02 x 49.02 | 21.02 x 24.49 x 52.99 |
| | Packing (WxDxH) | inch | 26.57x20.87x48.62 | 26.57x20.87x48.62 | 26.57x24.41x52.56 | 26.57x24.41x52.56 | 26.57 x 24.41 x 52.56 | 27.95 x 26.77 x 56.50 |
| | Net/Gross Weight | lbs | 106.48/131.61 | 106.48/132.72 | 128.53/157.41 | 129.63/154.10 | 132.50/156.75 | 164.02/190.48 |
| Outdoor Unit | Dimension (WxDxH) | inch | 35.04 x 13.46 x 26.50 | 37.24 x 16.14 x 31.89 | 37.24 x 16.14 x 31.89 | 37.24 x 16.14 x 31.89 | 37.48 x 16.34 x 52.48 | 37.48 x1 6.34 x 52.48 |
| | Packing (WxDxH) | inch | 40.55 x 18.11 x 29.13 | 42.91 x 19.88 x 35.04 | 42.91 x 19.88 x 35.04 | 42.91 x 19.88 x 35.04 | 43.11x19.49x57.48 | 43.11x19.49x57.48 |
| | Net/Gross Weight | lbs | 94.36/100.97 | 125.22/143.74 | 146.39/156.09 | 151.68/161.16 | 217.59/248.68 | 217.15/248.46 |
| AIRFLOW | | | | | | | | |
| Indoor air flow (Hi/Mi/Lo) | | m3/h | 980/900/840 | 1280/1160/1040 | 1520/1370/1210 | 1840/1650/1470 | 2180/1860/1540 | 2690/2310/1930 |
| | | CFM | 576.47/529.41/494.12 | 752.94/682.35/611.76 | 894.12/805.88/711.76 | 1082.35/970.59/864.71 | 1282.35/1094.12/905.88 | 1582.35/1358.82/1135. |
| Outdoor air flow | | m3/h | 3000 | 3800 | 5100 | 3800 | 7650 | 7500 |
| | | CFM | 1764.71 | 2235.29 | 3000 | 2235.29 | 4500 | 4411.76 |
| ESP Range | | Pa | 0-200 | 0-200 | 0-200 | 0-200 | 0-200 | 0-200 |
| REFRIGERA | NT & PIPING | | | | | | | |
| Refrigerant Charge | | 0Z | R410A/56.44ozs | R410A/81.13ozs | R410A/111.11ozs | R410A/130.51ozs | R410A/165.79ozs | R410A/172.84ozs |
| Piping Size Liquid Side/Gas Side | | inch | 1/4"-1/2" | 3/8"-5/8" | 3/8"-5/8" | 3/8"-3/4" | 3/8"-3/4" | 3/8"-7/8" |
| 1 9 | | : | , -,- | , -,- | , -,- | , -, - | , - | |

^{**25&#}x27; Quick Connect Line Set is not included with 36K, 48K, and 60K units. Those models are compatible with the MRCOOL® No Vac® Quick Connect Line set available for purchase separately.

