





Smart Home & NVR compatible

 KNX, Loxone, Synology, KIWI, AVM FRITZ!Fon, Control4, RTI, Bang & Olufsen, URC, QNAP, ELAN, Fibaro and others



Open API & SIP

 Interface for integration with additional third-party systems and SIP

IP VIDEO DOOR STATIONS - SINGLE-FAMILY RESIDENCES

D1101V

- Small and compact
- 1 call button
- 1 relay
- 1080p camera
- PoE and WiFi capable
- Available in stainless steel and bronze finish
- Flush-mount option available



D1101FV Fingerprint 50

- Small and compact
- 1 call button
- 1 relay
- 1080p camera
- Fingerprint reader
- PoE and WiFi capable
- Available in stainless steel and bronze finish
- Flush-mount option available



D1101KH Classic

- Small and compact
- 1 call button
- 1 relay
- 1080p camera
- Keypad module
- Stainless steel
- Surface-mount option available



D2101V

- 1 call button
- 2 relays
- RFID reader
- PoE capable
- Stainless steel
- More than 50 colors and finishes



D2101FV Fingerprint 50

- 1 call button
- 2 relays
- RFID reader
- Fingerprint reader
- PoE capable
- Stainless steel
- More colors available



D2101KV

- 1 call button
- 2 relays
- RFID reader
- Keypad module
- PoE capable
- Stainless steel
- More colors available



IP VIDEO DOOR STATIONS - MULTI-TENANT RESIDENCES

D2103V

- 3 call buttons
- 2 relays
- PoE capable
- Available with up to 18 call buttons
- Stainless steel
- More colors available



D21DKV and D21DKH

- For up to 100 units/apartements
- 2 relays
- RFID reader
- Display module
- Keypad modulePoE capable
- Available in stainless steel and bronze finish







IP ACCESS CONTROL SYSTEMS

- Stand-alone keypad
- 2 relays
- 125 KHz and 13.56 MHz RFID reader
- PoE and WiFi capable
- Surface-mount, flushmount and retrofit version available
- Stainless steel
- More colors available



INDOOR STATIONS

- PoE and WiFi capable
- 4" True Color Touch Display
- Room to room communication
- Supports multiple DoorBird IP Video **Door Stations**
- Available in black and white





Table stand A8003 available separately

A8005 Dual-Frequency RFID Transponder Key Fob, 125 KHZ (EM4100) and 13,56 MHz (MIFARE® DESFire® EV2 8K) for D21x and A1121





A1071 2-Wire Ethernet PoE converter





