


Floor lamp with direct and indirect light. Diffuser and rod made of fibreglass-based composite material and liquid coated. Translucent polycarbonate upper diffuser disc, PMMA lower diffuser disc with polyprismatic internal surface. Epoxy powder coated metal round base. Supplied with 4 counter-weights to be inserted in the purpose-provided seat above the diffuser to adjust its height. For LED version the circuit boards were purpose-designed by Foscarini, to achieve a superior level of color rendering (CRI) and retaining the same colour temperature as a halogen light source (Kelvin). The two LED circuit boards are installed on an aluminium disc that acts as a dissipator, and the upper board is protected by a small PMMA disc. Additional arc-extending rods available upon request; the black cable is fitted with a dimmer which can be used both to adjust the level of luminous intensity gradually or as the ON/OFF switch.

Twiggy

SCHEMATIC & LIGHT EMISSION



MATERIAL

Coated fiberglass-based composite material, PMMA, polycarbonate, coated metal and aluminium (LED)

COLORS



ACCESSORIES

Twiggy

LIGHT SOURCE

77WE27
Dimmer incluso

CERTIFICATIONS




ENERGY EFFICIENCY

A+, A

Twiggy LED

SCHEMATIC & LIGHT EMISSION



MATERIAL

Coated fiberglass-based composite material, PMMA, polycarbonate, coated metal and aluminium (LED)

LIGHT SOURCE

28W
2700 K 3840 lm CRI>90
dimmer included

COLORS



CERTIFICATIONS



ACCESSORIES


Twiggy

ENERGY EFFICIENCY

A+

Twiggy LED MyLight

SCHEMATIC & LIGHT EMISSION



MATERIAL

Coated fiberglass-based composite material, PMMA, polycarbonate, coated metal and aluminium (LED)

LIGHT SOURCE

28W
2700 - 5000 K 3840 lm CRI>90
Dimmable via Bluetooth with Casambi App

COLORS



CERTIFICATIONS



ACCESSORIES

Twiggy

ENERGY EFFICIENCY

A+