CIS SECURE TSG Poly CCX 600

CIS Secure introduces the first Teams-native TSG phone that brings you one-touch access to all of your contacts and meetings. Securely.



Soon and the second sec

Benefits

Eliminate distracting background noise at the source with Poly Acoustic Fence technology

Easy to manage with robust provisioning and management of telephony deployment and support

Conversations stay on track. Hear every nuance with the industry-leading sound quality, featuring Poly HD Voice.

Product Overview

The Poly CCX 600 Business Media Phone delivers high quality performance for workers in private offices and in open cubicle environments. The CCX 600 is designed to deliver a simple and intuitive experience for medium/high volume users from knowledge workers to contact center agents who need a full range of collaboration features. The CCX 600 provides system flexibility by being able to connect seamlessly as a Microsoft Teams-native endpoint or to other call control systems using Session Initiation Protocol (SIP).

CIS Secure enhances the full featured Poly CCX 600 to make it TSG compliant by modifying the phone to include Positive Disconnect functionality. The CIS Secure DTD-CCX600 delivers additional security by offering additional options including removed microphone, disabled speakerphone and additional network interface options for maximum flexibility. As part of our Desktop solution offerings, CIS Secure enables you to confidently communicate using your own optimized workflow. Our DTD-CCX600 is designed to allow you to leverage the comprehensive collaboration capabilities of the Microsoft Teams platform with the security of the mission in mind.

Key Features





in

CIS SECURE TSG Poly CCX 600

Product Specifications

Phone Options	Class A TSG #	Class B TSG #
 (2) 10/100/1000 RJ-45 Ports, Manual (2) 10/100/1000 RJ-45 Ports, Auto 2) 10/100/1000 RJ-45 Ports, Manual, Mic Removed (2) 10/100/1000 RJ-45 Ports, Auto, Mic Removed (2) 10/100/1000 RJ-45 Ports, Manual, Speakerphone Disabled, Mic Removed (2) 10/100/1000 RJ-45 Ports, Auto, Speakerphone Disabled, Mic Removed 	Coming Soon Coming Soon Coming Soon Coming Soon Coming Soon Coming Soon	TSG-B-11-2022 TSG-B-12-2022 TSG-B-13-2022 TSG-B-14-2022 TSG-B-15-2022 TSG-B-16-2022

*Class A phones include power injector, Class B phones PoE optional power supply

User Interface	Gesture-based, multitouch-capable touchscreen 7-inch color LCD (1024 x 600 pixel) 16:9 aspect ratio On-screen virtual keyboard Adjustable font size selection (regular, medium, large) Multilingual user interface	
Security	802.1X authentication and EAPOL media encryption via SRTP Transport layer security (TLS) Encrypted configuration files HTTPS secure provisioning Support for signed software executables	
Handset / Headset Port	RJ9 Interface / RJ9 Interface	
Dimensions (with handset)	26.3 cm x 21.7 cm x 6.0 cm WxHxD (10.4 in x 8.5 in x 2.4 in WxHxD)	
Weight	4.44 lbs.	
Operating Temp	32°F to 104°F (0° to 40°C)	
Warranty	Standard 1 year parts and labor Optional 3 years parts and labor	

CIS Secure Computing, Inc 21050 Ashburn Crossing Drive, Suite 145 Ashburn, VA 20147 (703) 996-0500 www.cissecure.com

