

The TSG Protected Conference Room



Collaboration with team members often happens in a conference room. The TSG certified CIS Secure Cisco 8832 ensures those discussions are secure



Benefits

Provides coverage for 24 x 30 foot room with 22-participants with Wired Mic Pods

Easy management and provisioning when used with Cisco Unified Communications Manager

Delivers robust audio features including comfort noise generation, silence suppression, echo suppression and dynamic noise reduction

Product Overview

The best collaboration often comes when a team is gathered together in the same room, leading to faster decision making and more productive interactions. When in a group setting and engaging with remote callers, the quality of your conference phone can and will directly impact the quality and experience of your phone call. The Cisco IP Conference Phone 8832 provides a simple, flexible, scalable solution that meets the challenges of the most diverse rooms. This loudspeaker architecture and microphones in the Cisco 8832 provide a dynamic, detailed sound with exceptional clarity, making conferencing an in-person experience with clear and natural audio quality.

CIS Secure ensures that collaboration with callers in a conference room setting is done securely with the DTD-8832. By optimizing the Cisco 8832 with TSG-approved on-hook security controls and other protection mechanisms, the DTD-8832 enables government users to securely communicate in areas where sensitive government information is discussed. The DTD-8832 delivers a clear and rich collaboration experience in executive offices, conference rooms and boardrooms.

Key Features



360-degree room coverage



3.9" Color Screen



Wired Mic Pods



SIP Capable



Programmable Soft Keys



The TSG Protected Conference Room

Product Specifications

	Class B	Class A
Part # (Manual)	DTD-8832-01	DTD-8832-02
TSG #	TSG-B-03-2022	TSG-A-05-2022
Part # (Automatic)	DTD-8832-01-A	DTD-8832-02-A
TSG #	TSG-B-04-2022	TSG-A-06-2022
Network	10/100/1000 Base T (PoE / RJ-45), (Class A includes CIS PoE Injector)	
Call Control Support	Native support in Cisco Unified Communications Manager 12.0(1); DevPack required for Cisco Unified Communications Manager 10.5.2, 11.0, and 11.5	
Acoustics	Frequency: 100 Hz to 20 kHz; microphones, 100 Hz to 12 kHz, ±3 dB Max adjustable volume: 89 dB within 0.5 m	
Dimensions (with handset)	10.9 x 10.9 x 3.4 in. W x L x H (278 x 278 x 86 mm)	
Weight	4.5 lbs.	
Operating Temp	32°F to 104°F (0° to 40°C)	
Warranty	Standard 1 year parts and labor Optional 3 years parts and labor	