



## Mobile Secure Video and Computer Travel Case w/ Intel Nuc (Model Number: DTD-SVV8841-6)

---

### Key Features

- Touchscreen control for Both the NUC and VTC
- Type 1 encryption capability KG-250Xs and KG-175n compatible
- Simple one case solution for VoIP, Data and VTC communications in the field
- Intel NUC7i5BNH Embedded Computer, 16Gb RAM, 500Gb SSD (NVMe option available)



### Short Description

The DTD-SVV8841-6 is a non-TEMPEST viable solution for secure mobile communications supported by Type 1 encryption capabilities (KG-250Xs/175n not included), an internal Red Trendnet gigabit switch well as a Black Cisco 5915 embedded service router to provide the mission-critical features needed while in the field. Designed within a ruggedized case, it bolsters a Cisco 8841 IP phone and 15.6" LCD touchscreen display to simplify constant communication when needed. The DTD-SVV8841-6 provides a single secure communications source for mobility and meets all your mission requirements even in the most challenging environments.

---

All TEMPEST solutions and services available from CIS Secure Computing are CTP II certified by CIS Labs, Inc., a wholly owned subsidiary of CIS Secure Computing, Inc. CIS Labs is a member of the NSA Certified TEMPEST Manufacturer and Test facility program.

---

### Contact Us

CIS Secure Computing, Inc.  
21050 Ashburn Crossing Drive  
Suite 145  
Ashburn, VA 20147

Phone: (703) 996-0500  
Fax: (703) 996-1111  
eFax: [fax@cissecure.com](mailto:fax@cissecure.com)  
Website: <http://www.cissecure.com>



## Mobile Secure Video and Computer Travel Case w/ Intel Nuc

<b>Interfaces</b>	(3) USB A ports (NUC) (1) Console port (Black Router, RJ45) (1) WAN port (RJ45) (1) Black data port (RJ45) (1) Red data port (RJ45) Headset and Handset ports (Cisco 8841)
<b>Network Standards (Trendnet switch)</b>	IEEE 802.3 10Base-T; IEEE 802.3u 100Base-TX IEEE 802.3ab 1000Base-T; IEEE 802.3x Flow Control
<b>Video Standards and Protocols</b>	H.264, H.264 High Profile Dual: H.239 (H.323); BFCP (SIP) SVC (Scalable Video Coding) H.263+ is supported with resolutions up to 4CIF@15fps. Only RFC2429 is supported. Custom formats and annexes are not supported.
<b>Live Video Resolutions</b>	1920 x 1080p @ 25, 30fps 1280 x 720p @ 25, 30fps 1024 x 576p @ 25, 30fps: w576p 848 x 480p @ 25, 30fps: w480p 768 x 448p @ 25, 30fps: w448p 704 x 576p @ 25, 30fps: 4CIF 704 x 480p @ 25, 30fps: 4SIF 624 x 352p @ 25, 30fps: w352p 576 x 336p @ 25, 30fps 512 x 288p @ 25, 30fps: wCIF 416 x 240p @ 25, 30fps: w240p 400 x 224p @ 25, 30fps 352 x 288p @ 25, 30fps: CIF 352 x 240p @ 25, 30fps: SIF
<b>Audio Protocols</b>	G.711 G.719 G.728 and G.729 A/B G.722, G.722.1, G.722.1 Annex C Opus
<b>Dimensions (H x W x D)</b>	7 x 18 x 15
<b>Power</b>	110-220 VAC Auto Switching
<b>Weight</b>	18 lbs.
<b>Warranty</b>	Standard 1 year parts and labor Optional 3 years parts and labor