

# SECURE TSG Poly CCX 500



CIS Secure introduces the first Poly CCX series TSG phone that brings you one-touch access to all of your contacts and meetings. Securely.



## Benefits

Eliminate distracting background noise at the source with Poly Acoustic Fence technology

Easy to manage with robust provisioning and management of telephony deployment and support

Conversations stay on track. Hear every nuance with the industry-leading sound quality, featuring Poly HD Voice.

## Product Overview

The Poly CCX 500 Business Media Phone delivers high quality performance for workers in private offices and in open cubicle environments. The CCX 500 is designed to deliver a simple and intuitive experience for medium/high volume users from knowledge workers to contact center agents who need a full range of collaboration features. The CCX 500 provides system flexibility by being able to connect seamlessly as an endpoint for any control systems using Session Initiation Protocol (SIP).

CIS Secure enhances the full featured Poly CCX 500 to make it TSG compliant by modifying the phone to include Positive Disconnect functionality. The CIS Secure DTD-CCX500 delivers additional security by offering additional options including a removed microphone, disabled speakerphone and additional network interface options for maximum flexibility. As part of our Desktop solution offerings, CIS Secure enables you to confidently communicate using your own optimized workflow. Our DTD-CCX500 is designed to allow you to leverage the comprehensive capabilities of your collaboration platforms with the security of the mission in mind.

## Key Features



Multi-Gesture Capable



5" Color Touchscreen



Headset Ready



SIP Capable



Poly HD Audio



# SECURE TSG Poly CCX 500

## Product Specifications

	Class B Compliant	Class A Compliant
Part # - 10/100/1000 Base TX	DTD-CCX500-01 (TSG # TSG-B-05-2022)	Coming Soon
Part # - 100 MB SC Fiber		Coming Soon
Part # - 1G SC Fiber		Coming Soon
Options Available	Microphone removed, speakerphone disabled, auto engage	
User Interface	Gesture-based, multitouch-capable touchscreen 5-inch color LCD (720 x 1280 pixel) 9:16 aspect ratio On-screen virtual keyboard Adjustable font size selection (regular, medium, large) Multilingual user interface	
Security	802.1X authentication and EAPOL media encryption via SRTP Transport layer security (TLS) Encrypted configuration files HTTPS secure provisioning Support for signed software executables	
Handset / Headset Port	RJ9 Interface / RJ9 Interface	
Dimensions (with handset)	17.8 cm x 21.6 cm x 5.2 cm WxHxD (7.0 in x 8.5 in x 2.0 in WxHxD)	
Weight	2.9 lbs.	
Operating Temp	32°F to 104°F (0° to 40°C)	
Warranty	Standard 1 year parts and labor Optional 3 years parts and labor	