





Selection chart for equipment and cabinets

configure your LCS² system (continued)

RJ 45 PATCH CORDS AND USER CORDS (p. 669, 673, 679)						LCS² cat. 6 _A	LCS² cat. 6	LCS² cat. 5e		
		S/FTP	Impedance 100 ohms	1 m		0 517 80	0 517 52	-		
				2 m		0 517 81	0 517 53	-		
				3 m		0 517 82	0 517 54	-		
				5 m		0 517 83	0 517 55	-		
		F/UTP	Impedance 100 ohms	1 m		-	0 517 62	0 516 40		
				2 m		-	0 517 63	0 516 41		
				3 m		-	0 517 64	0 516 42		
				5 m		-	0 517 65	0 516 43		
		U/UTP	Impedance 100 ohms	1 m		0 518 82	0 517 72	-		
				2 m		0 518 83	0 517 73	-		
				3 m		0 518 84	0 517 74	-		
				5 m		0 518 85	0 517 75	-		
		S/FTP	Impedance 100 ohms	1 m	RAL 3020	0 518 70	-	-		
					RAL 6026	0 518 66	-	-		
				2 m	RAL 3020	0 518 71	-	-		
					RAL 6026	0 518 67	-	-		
				3 m	RAL 3020	0 518 72	-	-		
					RAL 6026	0 518 68	-	-		
				5 m	RAL 3020	0 518 73	-	-		
					RAL 6026	0 518 69	-	-		
				F/UTP	Impedance 100 ohms	1 m	RAL 3020	-	0 518 54	-
							RAL 6026	-	0 518 50	-
						2 m	RAL 3020	-	0 518 55	-
							RAL 6026	-	0 518 51	-
		3 m	RAL 3020			-	0 518 56	-		
			RAL 6026			-	0 518 52	-		
		5 m	RAL 3020			-	0 518 57	-		
			RAL 6026			-	0 518 53	-		
		U/UTP	Impedance 100 ohms			1 m	RAL 3020	0 518 78	0 518 62	-
							RAL 6026	0 518 74	0 518 58	-
						2 m	RAL 3020	0 518 79	0 518 63	-
							RAL 6026	0 518 75	0 518 59	-
				3 m	RAL 3020	0 518 80	0 518 64	-		
					RAL 6026	0 518 76	0 518 60	-		
				5 m	RAL 3020	0 518 81	0 518 65	-		
					RAL 6026	0 518 77	0 518 61	-		

COPPER CABLES (305 OR 500 M REELS) (p. 669, 673, 679)						
	S/FTP	4 pairs	500 m	0 327 77	-	-
	SF/UTP	4 pairs	500 m	-	0 327 57	-
		2 x 4 pairs	500 m	-	0 328 59	-
	F/UTP	4 pairs	305 m	-	0 328 56	0 327 52
		4 pairs	500 m	0 327 78	0 327 56	0 328 50
		2 x 4 pairs	500 m	0 328 78	0 327 76	0 327 74
		305 m	-	0 327 54	0 327 50	
	U/UTP	4 pairs	500 m	0 327 87	0 328 61	0 328 53
		2 x 4 pairs	500 m	-	0 328 63	0 327 73

FIBRE OPTIC PATCH CORDS (p. 691)				OS1/OS2 (UPC) singlemode 9/125 µm	OM4 multimode 50/125 µm	OM3 multimode 50/125 µm
		SC/SC duplex cords	1 m	0 326 00	0 326 30	0 326 09
			2 m	0 326 01	0 326 31	0 326 10
			3 m	0 326 02	0 326 32	0 326 11
		SC/LC duplex cords	1 m	0 326 03	-	0 326 12
			2 m	0 326 04	-	0 326 13
			3 m	0 326 05	-	0 326 14
		LC/LC duplex cords	0.5 m	0 326 28	0 326 33	-
			1 m	0 326 06	0 326 34	0 326 15
			2 m	0 326 07	0 326 35	0 326 16
			3 m	0 326 08	0 326 36	0 326 17
			5 m	0 326 29	0 326 37	-

OPTICAL CABLES (REEL) (p. 684)						
	Indoor/Outdoor	6 fibres	0 325 12	0 326 65/66	0 325 10	
		12 fibres	Loose tube	0 325 14	-	-
			Tight buffer	0 325 50	0 326 67	0 325 11
		24 fibres	Loose tube	0 325 51	-	0 325 53
			Tight buffer	-	0 326 68	0 325 52
		Outdoor, reinforced steel, anti-rodent	6 fibres	0 325 13	-	-
			12 fibres	0 325 15	-	-