



Polycom VVX450 TSG Approved IP Phone

Key Features

- 4.3" Color LCD Display
- Built-in 10/100/1000 Ethernet switch for PC connection
- 12 line keys
- HD Voice up to 7kHz on all audio paths
- Open SIP and Skype for Business versions
- Supports VVX EM50 Expansion Module (2)
- Designed to meet CNSI 5001 on-hook security
- SIP Protocol Support, SDP, IETF SIP, RTCP & RTP support



Additional Features

- The speakerphone function is enabled and protected with the TSG on-hook security. It can be ordered without the microphone (listen-only speakerphone) or with the speakerphone button disabled.

The Polycom VVX450 supports Session Initiation Protocol (SIP), Session Description Protocol (SDP), IPv4, and IPv6. This Polycom VVS450 phone is a modified version that connects to your network like any other VVX450 phone. The difference is the addition of Positive Disconnect On-Hook Security. The on-hook security can be triggered automatically via the handset hook switch (Auto mode, part numbers differ) or manually disengaged after an off-hook condition is established (Manual mode). The mode is set at the factory and must be specified at time of order. The security re-engages automatically once any on-hook status is established. The phone also allows the on-hook security features to be engaged while in a call providing enhanced "Hold" and "Mute" security.

Contact Us

CIS Secure Computing, Inc.
21050 Ashburn Crossing Drive
Suite 145
Ashburn, VA 20147

Phone: (703) 996-0500
Fax: (703) 996-1111
eFax: fax@cissecure.com
Website: <http://www.cissecure.com>



Polycom VVX450 TSG Approved IP Phone

	TSG Class A Polycom VVX450 VoIP Phone	TSG Class B Polycom VVX450 PoE VoIP Phone
Standard	DTD-VVX450-02 NTSWG# TSG-A-67-2019	DTD-VVX450-01 NTSWG# TSG-B-61-2019
With Microphone Removed	DTD-VVX450-02-MR NTSWG# TSG-A-69-2019	DTD-VVX450-01-MR NTSWG# TSG-B-63-2019
With Speakerphone Disabled	DTD-VVX450-02-SD NTSWG# TSG-A-71-2019	DTD-VVX450-01-SD NTSWG# TSG-B-65-2019
Standard Auto	DTD-VVX450-02-A NTSWG# TSG-A-68-2019	DTD-VVX450-01-A NTSWG# TSG-B-62-2019
With Microphone Removed Auto	DTD-VVX450-02-MR-A NTSWG# TSG-A-70-2019	DTD-VVX450-01-MR-A NTSWG# TSG-B-64-2019
With Speakerphone Disabled Auto	DTD-VVX450-02-SD-A NTSWG# TSG-A-72-2019	DTD-VVX450-01-SD-A NTSWG# TSG-B-66-2019
Power	Includes Power Injector required for Class A deployment (DTD-VOIP-PI-02) Input: 100-240vAC, 50-60Hz Output: 48vDC @ 0.3a	Power over Ethernet (Standard) 13W max Optional universal AC power supply POWS067 Input: Universal AC Output: 5vDC @3A
Handset	Wideband handset	
Headset	No headset available	
Speakerphone	Polycom® HD Voice™ full-duplex speakerphone	
LAN and PC Ports	2-port Ethernet switch (connects phone and PC over a single line) LAN Port 10/100/1000Mb RJ45 PC Port 10/100/1000Mb RJ45	
Keys	12 line keys, soft keys, back, navigation cluster, home, transfer, messages, hold/ resume, dial pad, volume-control toggle, headset, speakerphone, and mute	
Dimensions (H x W X D)	10.0" x 9.5" x 2.2"	
Weight	2.25 lbs. (2.75 with Class A Power Injector)	
Temperatures	Operating: 32 to 104°F (0 to 40°C) Non-operating: 14 to 140°F (-10 to 60°C)	
Humidity	10 to 95%, noncondensing	
Backlit Indicators	Line keys, message waiting, audio path keys (handset, headset, and speakerphone)	
Warranty	Standard 1 year parts and labor Optional 3 years parts and labor	