

LEDA Outdoor

120v : **3-712-2xx**

277v : **37-712-2xx**

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____



-24 Satin Nickel



-22 Oiled Bronze

LIGHT SOURCE 1 x 10.1W LED, 3000K, CRI 90

LUMINAIRE POWER 13.0W at 120V

RATED LIFE 60000 hr RL

OPTIONAL COLOR TEMPERATURES 2700K, 3500K, 4000K

LUMEN OUTPUT Delivered: 680 lm (LM-79)

INPUT VOLTAGE 120V or 277V

DRIVER OUTPUT 350 mA, 12W

DIMMING 0-10v & Phase (ELV) Dimming - 50/60Hz 100% to 10% Dimming



CONSTRUCTION Cast Aluminium and Acrylic

DIFFUSER -2 Matte White Acrylic

FINISHES Oiled Bronze (-22), Satin Nickel (-24)

MOUNTING 4" Octagonal J-Box
(Installer must provide a bead of caulk between fixture housing and mounting surface)

STANDARDS ETL Wet, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



DIMENSIONS

W: 7.25"

H: 16.50"

Ext: 4.75"

M.C: 8.25" From top of fixture

Order example for standard fixture:
3-712-224 (x- Voltage - xxx-Sequence # - x-Diffuser - xx-Finish)
 3: 120v, 37: 277v
 Order example for optional color temperatures: **3-712-27224**
 27: 2700K, 35: 3500K, 40: 4000K

