

STANDARD FEATURES

- . ₩.HESTAN
- Horizon HoodTM with spring-assisted hinges to hold at desired heights*
- Motion activated Stadium LightsTM with halogen under-hood lighting*
- Multi-purpose built-in ceramic infrared rotisserie / searing / finishing burner* from 12,000 to 18,000 Btu/hour (depending on model) with simple touch on function
- High performance 321SS tubular Trellis BurnerTM at 25,000 Btu/hour each*
- 5/16" thick stainless steel DiamondCut GratesTM lasered in-house*
- Hot surface ignition system with lighting assist function







Multi-Purpose Ceramic Infrared Rotisserie



• High performance variable ceramic infrared sear burner at 25.000 Btu/hour each

- · Symmetrical flip to clean radiant tray with monogrammed ceramic briquettes*
- 519 square inch total grilling surface for 30" model. 647 square inch total grilling surface for 36" model. 774 square inch total grilling surface for 42" model.
- Available in 30", 36", and 42" widths
- 12" built-in double side burners or stainless steel worktop with storage drawer
- MarquiseTM accented panels, side cart handle, and commercial end caps
- Flip-down front panel with commercial grade handle for access to gas tank and pullout tool storage drawer
- Standard pullout tray for LP gas tank through rear access door
- Left side MarquiseTM paneled fold-down side shelf for extra work space
- Extra-large gray front wheels and commercial grade gray casters with 360 degrees of maneuverability for the smoothest cart movement











- Concealed chain driven whisper quiet rotisserie motor system with a single speed, 6 rpm, 50 in-lbs motor
- Double side burners: 20,000 Btu/hour brass front burner and 10,000 Btu/hour brass rear burner
- 5/16" thick DiamondCut GrateTM
- · Sealed burner bowl with drain tube for easy cleaning
- Electronic spark ignition system with re-ignition capability
- · LED lighting on front control panel
- 120V, 60Hz, 7 amp
- Please refer to Built-In Grills and Side Burner spec sheets for additional features





Shown with side burner





OPTIONS & ACCESSORIES

- Natural Gas (NG) or Liquid Propane (LP)
- Twelve (12) Hestan signature color finishes
- Carbon Fiber Vinyl Cover
- Gas conversion kits (NG/LP)
- · Variable Sear conversion kit
- Trellis BurnerTM conversion kit
- High Altitude Kit



All Models	Description	Overall Dims W(in.) x D(in.) x H(in.)	Total Btu's
G_BR3oCX-NG / -LP	Deluxe Freestanding 30" grill with worktop / drawer	48- ³ / ₄ 32- ¹ / ₂ 53- ⁹ / ₁₆	62000
G_BR30CX2-NG / -LP	Deluxe Freestanding 30" grill with double side burner	48- ³ / ₄ 32- ¹ / ₂ 53- ⁹ / ₁₆	92000
G_BR ₃ 6CX-NG / -LP	Deluxe Freestanding 36" grill with worktop / drawer	54 ⁻³ /4 32 ⁻¹ /2 53 ⁻⁹ /16	89000
G_BR36CX2-NG / -LP	Deluxe Freestanding 36" grill with double side burner	54 ⁻³ / ₄ 32 ⁻¹ / ₂ 53 ⁻⁹ / ₁₆	119000
G_BR42CX-NG / -LP	Deluxe Freestanding 42" grill with worktop / drawer	60- ³ /4 32- ¹ /2 53- ⁹ /16	118000
G_BR ₄₂ CX ₂ -NG/-LP	Deluxe Freestanding 42" grill with double side burner	60- ³ / ₄ 32- ¹ / ₂ 53- ⁹ / ₁₆	148000

_= specify burner configuration

A= all Trellis Burners M= Sear and Trellis Burners S= all Sear Burners

ELECTRICAL REQUIREMENTS:

120V, 60Hz, 7 amps

GAS REQUIREMENTS: 1/2" NPT gas connection. Minimum gas supply is 7" water column for natural gas and 11" for propane. Operating pressure at the manifold is 4" water column for natural gas and 10" for propane.

All units require a regulated gas supply. (included)

Hestan Outdoor products are approved for outdoor use only. Hestan Commercial Corporation reserves the right to change materials and specifications without notice. Specify type of gas when ordering.