


## TECHNICAL SPECIFICATIONS:


- HIGH FIRE 53,000BTU/HR (NG) 47,000BTU/HR (LPG)
- LOW FIRE 46,000BTU/HR (NG) 40,000BTU/HR (LPG)
- MANIFOLD PRESSURE: NG -5.5" W.C. (HI), 4.0" W.C. (LO) | LPG -9.8" W.C. (HI), 7.0" W.C. (LO)
- GAS SUPPLÝ PRESSURÈ: ŃG -6.5" W.C. (MIN), 14.0" W.C. (MAX) | LPG: 11.0" W.C. (MIN), 14.0" W.C. (MAX)
- ELECTRICAL SUPPLY: 24 VOLTS, 0.8 AMPS
- DIRECT SPARK IGNITION WITH 3-TRY LOCK OUT & AUTOMATIC RE-LIGHT

## WARRANTY:


- 3 YEARS ON 316 STAINLESS STEEL EMITTER
- 1 YEAR ON ALL OTHER PARTS

## OPTIONAL GAS CONNECTION COVER






ELEVATION HEAT COVERAGE




12'

TYPICAL COVERAGE TWO HEATERS

TYPICAL COVERAGE
ONE HEATER



FRONT ELEVATION - MODEL GA301-T



BOTTOM MOUNTING PLATE

## NOTES:

- INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWING.
- 3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5029-014.



5029-014 REVISION DATE 09/01/2018