

Battery Instructions

(LK-13)

Please Read Instructions Before Use

Kit Includes:

- 1 x Battery
- 1 x charger
- 1 x DC output cable
- 1 x Instruction sheet

Product Specifications:

Model	PWR-12V-B38
Capacity	3500mAh
Battery Cell	Li-ion
Shell Material	ABS
Dimension	3.8"x2.3"x0.9"
Weight	6 oz.
Color	Black
Input	DC 12.6V/350mA-2000mA
Output	DC 9-12.6 mA/1000mA-2000mA
Operating Temp.	50 – 113°F
Storage Temp	50 – 140°F
Power Efficiency	>90%
Safety Protection	Over Charge, over Discharge, Over Current, Short Circuit

Charging Instructions:

- Plug charger into wall outlet, LED indicator on charger will be green.
- Plug battery pack into charger, flip switch into on position (–). LED indicator will be RED for a charging battery.
- LED indicator on charger will turn GREEN when charging is complete.
- During charging place battery pack on a smooth hard surface to avoid overheating.

Warning:

- Do not use battery in high humidity, or wet locations.
- Do not modify or disassemble battery pack.
- Keep battery pack away from hot surfaces and open flames.
- Do not use battery pack if damaged, this could lead to leakage, heat or ignition.
- Do not charge battery on surfaces such as; carpet, linens or other flammable surfaces.

Battery Instructions

(LK-13)

Please Read Instructions Before Use

Kit Includes:

- 1 x Battery
- 1 x charger
- 1 x DC output cable
- 1 x Instruction sheet

Product Specifications:

Model	PWR-12V-B38
Capacity	3500mAh
Battery Cell	Li-ion
Shell Material	ABS
Dimension	3.8"x2.3"x0.9"
Weight	6 oz.
Color	Black
Input	DC 12.6V/350mA-2000mA
Output	DC 9-12.6 mA/1000mA-2000mA
Operating Temp.	50 – 113°F
Storage Temp	50 – 140°F
Power Efficiency	>90%
Safety Protection	Over Charge, over Discharge, Over Current, Short Circuit

Charging Instructions:

- Plug charger into wall outlet, LED indicator on charger will be green.
- Plug battery pack into charger, flip switch into on position (–). LED indicator will be RED for a charging battery.
- LED indicator on charger will turn GREEN when charging is complete.
- During charging place battery pack on a smooth hard surface to avoid overheating.

Warning:

- Do not use battery in high humidity, or wet locations.
- Do not modify or disassemble battery pack.
- Keep battery pack away from hot surfaces and open flames.
- Do not use battery pack if damaged, this could lead to leakage, heat or ignition.
- Do not charge battery on surfaces such as; carpet, linens or other flammable surfaces.

Battery Instructions

(LK-13)

Please Read Instructions Before Use

Kit Includes:

- 1 x Battery
- 1 x charger
- 1 x DC output cable
- 1 x Instruction sheet

Product Specifications:

Model	PWR-12V-B38
Capacity	3500mAh
Battery Cell	Li-ion
Shell Material	ABS
Dimension	3.8"x2.3"x0.9"
Weight	6 oz.
Color	Black
Input	DC 12.6V/350mA-2000mA
Output	DC 9-12.6 mA/1000mA-2000mA
Operating Temp.	50 – 113°F
Storage Temp	50 – 140°F
Power Efficiency	>90%
Safety Protection	Over Charge, over Discharge, Over Current, Short Circuit

Charging Instructions:

- Plug charger into wall outlet, LED indicator on charger will be green.
- Plug battery pack into charger, flip switch into on position (–). LED indicator will be RED for a charging battery.
- LED indicator on charger will turn GREEN when charging is complete.
- During charging place battery pack on a smooth hard surface to avoid overheating.

Warning:

- Do not use battery in high humidity, or wet locations.
- Do not modify or disassemble battery pack.
- Keep battery pack away from hot surfaces and open flames.
- Do not use battery pack if damaged, this could lead to leakage, heat or ignition.
- Do not charge battery on surfaces such as; carpet, linens or other flammable surfaces.

Battery Instructions

(LK-13)

Please Read Instructions Before Use

Kit Includes:

- 1 x Battery
- 1 x charger
- 1 x DC output cable
- 1 x Instruction sheet

Product Specifications:

Model	PWR-12V-B38
Capacity	3500mAh
Battery Cell	Li-ion
Shell Material	ABS
Dimension	3.8"x2.3"x0.9"
Weight	6 oz.
Color	Black
Input	DC 12.6V/350mA-2000mA
Output	DC 9-12.6 mA/1000mA-2000mA
Operating Temp.	50 – 113°F
Storage Temp	50 – 140°F
Power Efficiency	>90%
Safety Protection	Over Charge, over Discharge, Over Current, Short Circuit

Charging Instructions:

- Plug charger into wall outlet, LED indicator on charger will be green.
- Plug battery pack into charger, flip switch into on position (–). LED indicator will be RED for a charging battery.
- LED indicator on charger will turn GREEN when charging is complete.
- During charging place battery pack on a smooth hard surface to avoid overheating.

Warning:

- Do not use battery in high humidity, or wet locations.
- Do not modify or disassemble battery pack.
- Keep battery pack away from hot surfaces and open flames.
- Do not use battery pack if damaged, this could lead to leakage, heat or ignition.
- Do not charge battery on surfaces such as; carpet, linens or other flammable surfaces.