

Multi-mode super bright 36W 72 SMD site lamp

CE RoHs

Light Output

Single button controlled high quality output in multiple modes

	HIGH INTENSITY	MEDIUM INTENSITY	LOW INTENSITY
LUMEN	3000	1500	750
RUN TIME	1.5 hours	2.5 hours	5 hours

Sturdy Construction

- a. IP65 Rated
Protected against dust and effects of low pressure water jets from any direction
- b. Corrosion resistant aluminium die cast construction in premium powder coated finish
- c. Impact proof ABS frame
- d. Tempered glass lens
- e. Steel handle with foam grip for comfort in use
- f. Sturdy steel stand for balance positioning in the toughest of job site conditions


Patented Design

Unique & innovative 360° swivel & tilt mechanism. Stainless steel ball joint mechanism allows

- a. Swivelling of light full 360°
- b. Tilt



Power Source



Charging of Battery


Battery can be recharged using dual voltage 100V-240V AC charger, provided with the light

Charge Time

4.5 hours



Tilt & Swivel to 360°



Power Button

USB Port

3 LED battery level indicator
5V 2.1 Amp USB output port for use as power bank

FEATURES

MAX. LUMEN	WATER & DUST PROOF RATING	BEAM ANGLE	BEAM DISTANCE	OPERATING TEMPERATURE
3000	IP65	120°	45M (147')	-10°C TO 40°C (14°F TO 104°F)

ORDERING INFORMATION

CAT NR.	ORD NR.	SIZE (L×H×D)		BOX QTY.
		(INCH)	(MM)	
LED/660	55043	8.7 × 8.7 × 12.2	223 × 223 × 309	8

