



W&H MOLDER COMPARISON CHART

CHOOSE THE MOLDER THAT FITS YOUR NEEDS!

800-258-1380 local 603-732-0219

<u>FEATURES</u>	<i>MODEL 154CE</i>	<i>MODEL 206</i>	<i>MODEL 206 (50Hz Export)</i>	<i>MODEL 209</i>
<u>FEED TYPE</u>	11 (fpm) constant feed	0-19 (fpm) variable feed	0-19 (fpm) variable feed	0-19 (fpm) variable feed
<u>KNIFE MOTOR</u>	2 HP (3450 rpm)	2 HP (3450 rpm)	2 HP (3450 rpm) (50Hz Export)	1 1/2 HP (3480 rpm)
<u>SINGLE PHASE VOLTS FLA (Full Load Amps)</u>	Single Phase 208V (12.2 FLA) 240V (11.5 FLA)	Single Phase 208V (12.2 FLA) 240V (11.5 FLA)	Single Phase 240V (12.2 FLA) (50Hz Export)	Single Phase 115V (15.0 FLA) 20 AMP REQUIRED
<u>THREE PHASE VOLTS FLA (Full Load Amps)</u>	Not Available	Three Phase 208V,230V,260V (5.3fla,5.0fla,2.5fla)	Not Available	Not Available
<u>ARBOR RPM'S</u>	6900	6900	6900	6960
<u>MACHINE BASE</u>	Steel Construction with levelers	Steel Construction with levelers	Steel Construction with levelers	Steel Construction with levelers
Length/Width/Height	28"/22"/33"	28"/22"/33"	28"/22"/33"	28"/22"/33"
Working Height	35"	35"	35"	35"
Mobility	Optional mobile base Item# 54-400	Optional mobile base Item# 54-400	Optional mobile base Item# 54-400	Optional mobile base Item# 54-400
<u>GUIDE SYSTEM</u>	GS-2-1	GS-2-1	GS-2-1	GS-2-1
<u>PACKAGE WEIGHT</u>	Approx. 218 lbs	Approx. 218 lbs	Approx. 218 lbs	Approx. 218 lbs
<u>AVAILABILITY</u>	In-Stock	In-Stock	In-Stock	In-Stock

MOLDER SPECS FOR ALL MODELS

Maximum Profile Depth 3/4"
 Maximum Profile Width 6 3/4"
 Minimum Stock Length 9"
 Minimum Stock Thickness 1/4"
 Maximum Height Above Final Cut 3/16"
 Maximum Stock Thickness 8"
 Planes 7" Wide

ADDITIONAL ACCESSORIES

Custom & In-Stock Profile Knives
 Item# 54-400 Mobile Base
 Item# EJ-92 Elliptical Jig

**SIGN UP FOR OUR LOYALTY PROGRAM
 SAVE ON PROFILE KNIVES AND MORE**