

INSTALLATION INSTRUCTIONS

61501/62001-1A1C5

Dual USB Charger with 15/20A with Tamper Resistant Receptacle





61501-1A1C5 (15A)

62001-1A1C5 (20A)

WARNING

Turn the POWER OFF at the circuit breaker before installing the receptacle.

Read and understand these instructions before installing. This device is intended for installation in accordance with the National Electric Code and local regulations. It is recommended that a qualified electrician performs this installation. Make sure to turn off the circuit breaker or fuse(s) and make sure power is off before wiring the device.

Use copper wire only.

This USB receptacle CANNOT be used if the outlet you are replacing has the top and bottom outlets controlled by separate circuit breakers.

WIRING DIRECTIONS

1. Insert wire(s) through terminal holes in the back, then tighten terminal screws.

- Insert HOT wire to the HOT terminal
- Insert NEUTRAL wire to the NEUTRAL terminal
- Insert Ground wire to the GREEN screw


COMPATIBILITY

This High Speed Dual USB Charger/Tamper-Resistant Receptacle is compatible with a wide range of electronic devices including, but not limited to, the following:

- iPad[®]Pro
- iPad[®]Air
- iPad[®] Mini
- iPod[®]
- iPhone[®] 6/ 6 Plus
- Tablets
- Mobile Phones
- Bluethooth[™] Headsets
- Digital Cameras
- HTC One X9[™]
- HTC One S9

Nexus 6P

- Lenovo ZUK Z1
- Samsung Galaxy S4[™]
- Samsung Galaxy Note 3™
- Samsung Galaxy J7[™]
- Nook e-reader
- GPS Devices
- Other Smart Phones and USB
- Compatible products



WARRANTY INFORMATION

This device is warranted to be free of material and workmanship defects for 2 years from the date of purchase. Original receipt or proof of purchase from an authorized retailer must be presented upon warranty claim. ALL claims must be verified and approved by Enerlites, Inc. Warranties from other Enerlites products may vary. This warranty is nontransferable and does not cover normal wear and tear or any malfunction, failure, or defect resulting from misuse, abuse, neglect, alteration, modification, or improper installation. To the fullest extent permitted by the applicable state law, Enerlites shall not be liable to the purchaser or end user customer of Enerlites products for direct, indirect, incidental, or consequential damages even if Enerlites has been advised of the possibility of such damages. Enerlites' total liability under this or any other warranty, express or implied, is limited to repair, replacement or refund. Repair, replacement or refund are the sole and exclusive remedies for breach of warranty or any other legal theory.

SPECIFICATIONS

Receptacle Rating	
	Type A USB Port 5V/2.4A Type C USB Port 5V/3A
	Type A/C USB Port 5V/5A
Wire Terminals	#14-#12 AWG
Operating Temperature	
USB Compatibility	USB 1.1/2.0/3.0 devices, including Apple products
Receptacle dimension	

DESCRIPTION

The 61501/62001-1A1C5 is a duplex Tamper-Resistant Receptacle with two USB charging ports. Two individual high powered vertical USB Ports, one Type A deliver 2.4A or one Type-C deliver 3.0A. A combined total of 5A can charge any current USB compatible device simultaneously including smart phones, tablets, e-readers, cameras and MP3 players. It is also capable of charging new devices that require higher current ratings.

FEATURES

- Two USB ports with a total high-current power of 5 Amp, 5VDC.
- Separately, Type A USB output 2.4A or Type C output 3.0A
- Charges most USB compatible electrical devices directly without an adapter.
- 2011 NEC Code compliant Tamper-Resistant Shutters.
- Replaces a standard duplex receptacle.
- Back wire terminals are for quick and easy installation.

