



**Industrial Field & Hazardous Locations** 



### **Applications**

#### Oil and Gas industry

- All petroleum production and refining
- Petroleum loading and transportation
- Petroleum storage and retail
- LNG industry
- All mining operations and service Chemical industry
- · All types of paint facilities
- Chemical production and storage

#### Ocean, marine and aerospace field

- Ocean platform operation facilities and structure
- Aerospace clean room and production
- Ocean vessel operations

#### Metal treatment

- · Steel and aluminum factories
- Pumping stations in any environment
- Metal smelting, foundry and fabrication

#### Food and alcohol industry

- Flour and fine particle production and storage
- Food and distilling production
- Alcohol industry

Other high humidity, high dust, high temperature, vapor locations





### **Explosion Protection**

MarkingAtex II3 G Ex ec IIC T5/T6 Gc II2 D Ex tb IIIC T80/100°C Db IP66

Marking IECEX Ex ec IIC T5/T6 Gc Ex tb IIIC T80/100°C Db IP66

Marking UL844(North American) Class I, Division 2, Groups A, B, C, D Class II, Division 1, Groups E, F, G Class II, Division 2, Groups F, G Class III

Marking Marine UL1598, UL1598A **ABS** Other Rating **IP 66** 



















## **Specification**

Product Number	Wattage	Color Temperature	Voltage	Lumens	Warranty	CRI
EX-20W H2YZDA	20	2200K-7000K	AC100-277V IC 100-277V AC 200-480V DC 12-48V	2800	5 years	80
EX-40W H2YZDA	40			5600		
EX-40W H4YZDA	40			5600		
EX-60W H4YZDA	60			8400		
EX-80W H4YZDA	80			11200		


<sup>&</sup>quot;H2, H4"=Product code "Y"=D or N: Dimmable or Non-dimmable "Z"=CCT, from 2200~7000K "D"=Beam angle, D120 for 120°. A for cover info. blank for flat cover, C spherical cover.

### **Packing Information**

Model	Quantity/Ctn	Length(cm)	Width (cm)	Height(cm)	Net weight(kg)	Gross weight (kg)
H2	2	69.1	41.3	29	4	9
H4	2	130	40	29.5	5.5	14.5

## **Light Distribution**

#### 120D





#### **Features**

- Working Temperature: -40°C ~ +60°C.
- High quality SMT LED and Meanwell Driver.
- Light-weight design by aircraft aluminum.
- Heavy-duty and high impact resistance.
- Three connection cable entry points.
- Replaceable LED board and drivers.
- Integrated junction box for driver with emergency back up.
- Dimmable and battery back up function available.
- Marine rating powder coated appearance treatment.
- Up to 5 years limited warranty option.
- Emergency Battery back up to three hours.
- Various installation ways for different applications.
- Glass lens or Glass with polycarbonate lens to make bigger beam angle.




## Dimension Unit: mm or inch






# **Mounting**


No.1 Ceiling Mounting



No.2 Pole Bracket Mounting



No.3 Wall Mounting



#### **Accessories**



Bracket

Metal Conduit



Bended Pipe

