

OFFICE PRO® 60

MOVINGCOOL
THE #1 SPOT COOLING SOLUTION

Providing up to 60,000 Btu/h of cooling capacity, more than twice the cooling power of the Office Pro® 24, the Office Pro 60 portable air conditioner is specifically designed for large office spaces and computer rooms filled with heat-generating electronics. Computer networks, communications and office equipment will shut down and critical data will be lost when the temperature rises, crippling daily operations.

Avoid this situation by bringing portable air conditioning to just the area or room that needs it. The Office Pro saves money while protecting your company's investment in equipment and customers. Self-contained and portable, the Office Pro 60 requires no costly installation, simply roll it in, plug it in and turn it on.

- 24/7 programmable operating modes
- Provides 60,000 Btu/h of cool air, maximum spot cooling to just the room that needs it
- No costly installation necessary, simply roll it in, plug it in, turn it on
- Condensation pump included, pumps water to remote drain for uninterrupted operation
- Operates automatically after-hours or during weekends with easy-to-use controls



DENSO

TECHNICAL SPECS		OFFICE PRO® 60*
Electronic Features	Control	Programmable
Cooling Capacity	Rating Conditions: 95°F at 60% RH	60,000 Btu/h
Electrical Characteristics	Voltage Requirements Total Power Consumption Current Consumption Recommended Fuse Size NEMA Plug Configuration Min. – Max. Voltage	1 Phase, 208/230V 6.6 kW 29 amps 50 amps 6 - 50 198 - 250
Fans	Motor Output - high/low	0.5/0.33 kW (Evaporator) 1.2/0.93 kW (Condenser)
Evaporator	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 1940/1770 CFM 0.9 IWG
Condenser	Fan Type Max. Air Flow - high/low Max. External Static Pressure	Centrifugal 2830/2650 CFM 0.85 IWG
Compressor	Type Output	Hermetic Scroll 3.9 kW
Refrigerant	Type	R-410A
Dimensions	W x D x H	30 x 52 x 64 in
Net Weight/Shipping Weight		623/732 lb
Power Cord	Gauge/Length	6 AWG (3-core)/6 ft
Condensate Tank Capacity		Auto Pump Included
Operating Conditions	Min. – Max. (@ 50% RH)	65° - 105°F
Max. Equivalent Duct Length	Per Cold Duct Hose Hot Duct Hose	40 ft 100 ft
Max. Sound Level	With Condenser - Duct high/low Without Condenser - Duct high/low	69/67 dB(A) 71/69 dB(A)

*Specification information shown with 230V
Specifications subject to change without notice.

Distributed by:

Pure n Natural Systems, Inc.

1-800-237-9199
purennatural.com
Streamwood, IL 60107

360-0819-OP60

©2016 DENSO PRODUCTS AND SERVICES AMERICAS, INC.

MovinCool, Climate Pro, SpotCool and Office Pro are registered trademarks of DENSO Corporation.