

IMPORTANT

READ THIS INFORMATION BEFORE USING PRODUCT
NEVER operate this unit if it has a damaged plug, if it is not working properly, or if it has been damaged in any way.
NEVER operate this unit with the air openings blocked in any way. Allow a minimum of 18 inches of clearance in front of the unit at all times. Keep the air openings free from lint, dust and the like.

NEVER use outdoors.

- **WARNING**

NEVER, under any circumstances, place any object into the unit via the air holes while the unit is plugged in as they may touch dangerous voltage points. Doing so could result in serious shock or create a fire hazard.

- **WARNING**

ONLY plug this unit into a standard 120 VAC outlet. Under no circumstances whatsoever should any other power supply be used. A power supply with voltage greater than that specified for the unit can result in serious injury to the user. Voltages greater or significantly lower than that specified for the unit will result in irreparable damage to the unit and will void all warranties.

• **KEEP OUT OF REACH OF THE CHILDREN CAUTION!**

Under Normal operating conditions the NewAire Plug In produces minimal amounts of ozone. The Canadian Standards Association (CSA) warns that concentrations above 0.04 ppm may be injurious to health.

OPERATING INSTRUCTIONS

1. Read this pamphlet in its entirety before using your NewAire Plug In.

2. Plug your unit into any 120 VAC grounded outlet. Ideally, the outlet should be as high as possible and should be in an area free of any immediate obstruction.

3. Turn the unit on by depressing the on/off button. The green indicator light will illuminate steadily, indicating that the unit is turned on and is functioning properly. Since there are no moving parts or fan in this unit it will operate in total silence. Air movement is accomplished solely by use of electrical energy.

4. If the green light begins to blink on and off - refer to cleaning instructions.
5. You may notice arcing or snapping sounds from the cell. This may be caused by high humidity levels (over 80%) or when large particles of some sort have entered the unit. Excessive amounts will lead to a blinking green light (refer to cleaning instructions).

WARRANTY INFORMATION

The NewAirePlug In comes with a limited 2 year warranty as follows:

1. Complete and return enclosed Warranty Card within 60 days of purchase. Failure to do so will render all warranty conditions null and void.

2. This unit is warranted against defects in material or workmanship for a period of two years from the date of proof of purchase. Any problems arising from misuse, attempt at repair, damage due to dropping, shipping or exposure to any liquid immediately render this warranty null and void.

3. If you have a warranty situation, contact NewAire customer service toll free at (877) 646-9663.

4. NewAire, Inc. reserves the right to repair or replace any units which are covered under this warranty.

5. This warranty is in lieu of any and all other warranties, either expressed or implied. This included, but is not limited to, implied warranties of marketability of fitness for a particular purpose or function. In no event will NewAire be liable for any amount in excess of the original purchase price of the NewAire Plug In. No agent, dealer distributor or service company is authorized to change, modify or extend terms of this warranty in any manner whatsoever.

6. This warranty gives specific legal rights. You may also have other rights which vary from state to state. This warranty is valid for units sold in the United States of America and Canada only.

7. NewAire Plug In is a patented product of NewAire, Inc.

CLEANING & MAINTENANCE

DO NOT OPEN UNIT

Your NewAir® Plug In requires no maintenance other than the occasional cleaning of the steel ring located behind the air hole openings. The frequency of cleaning is entirely dependent upon the amount of dust, lint or other airborne particles present when the unit is in use.

Cleaning this unit is necessary when the green indicator light flashes on or off while the unit is in operation. This flashing light indicates a build-up of dust/debris on the inner surface of the steel ring.

To clean your unit, follow these instructions:

1. **ALWAYS** turn the unit off by depressing the on/off button and **UNPLUG THE UNIT FROM THE OUTLET.**

2. Sometimes the dust or lint can be removed by simply holding the unit up to your mouth and blowing short breaths of air into air hole openings. If the green light indicator stops blinking the cleaning is successful.

3. For more extensive cleaning, use a Q-tip dipped in rubbing

CUSTOMER SERVICE 800-237-9199

newaire™

New Aire Plug In units output negative ions and regulated amounts of ozone to eliminate odors and improve the aire quailty in rooms up to 500 sq. ft.

Perfect for:

- Kitchens
- Family Rooms
- Laundry Rooms
- Den/Smoking odors
- Hallways
- Hospitals
- Pet Areas
- Offices
- Nursing Homes
- Boats
- RV's
- Hotel Rooms

newaire™

The NewAire Plug In is a patented technology (Patent # 5,316,741) wholly owned by NewAire, Inc.,

OPERATING INSTRUCTIONS



CLEANING, MAINTENANCE & WARRANTY

AIR VENT

- Keep free of obstructions
- Preferably mount as high as possible
- Do not insert metal objects
- See cleaning instructions

Green Light Indicator

When green indicator is lit the unit is operating properly.

When green indicator is flashing, unplug the unit immediately as it requires cleaning or repair. See cleaning instructions.

SPECIFICATIONS
120 VAC. 35 mA .60 Hz 3W
2.5" x 3.5" x 5.5"
Made in U.S.A.

CAUTION HIGH VOLTAGE
CAUTION HIGH VOLTAGE LEVELS OF OZONE MAY BE INJURIOUS TO HEALTH, USE AS
DIRECTED IN WELL VENTILATED LOCATIONS.
ATTENTION DES CONCENTRATIONS EN OZONE ELEVEES PEUVENT ETRE DANGEREUSES
POUR LA SANTE, UTILISER SELON LES CONSIGNES DANS ENGIOITS BIEN VENTILES.
FOR COMMERCIAL USE ONLY AND NOT FOR RESIDENTIAL USE.
POUR USAGE COMMERCIAL SEULEMENT. NE PAS UTILISER DANS UN LOCAL D'HABITATION
CERTIFIED FOR SHOCK AND ELECTRICAL FIRE HAZARD ONLY.
LA CERTIFICATION CSA VISE UNIQUEMENT LES RISQUES DE CHOC ELECTRIQUE ET
D'INCENDIE.



SHOCK HAZARD DO NOT OPEN