Q'STRAINT




IMPORTANT SAFEGUARDS AND WARNINGS

- This is a quick guide which MUST first be read and understood before using this system.
- J-Hooks must be attached to a solid wheelchair frame (no spokes, wheels or movable components).
- This is **NOT** a securement system and should not be used during transportation.

BOARD WHEELCHAIR PASSENGER


- 1. Wheelchair behind ramp.
- 2. Lock brakes or power off chair.
- 3. Press and hold both buttons (4 sec) to release retractors.



DEBOARD WHEELHAIR PASSENGER




- 1. Wheelchair facing INQLINE Loader retractors.
- 2. Lock Brakes or power off chair.
- 3. Press and hold buttons (4 sec) to release retractors.
- 4. Attach front J-Hooks to solid frame (60 sec) and unlock chair.






- 4. Attach front J-Hooks to solid frame (60 sec).
- 5. Unlock brakes and keep chair powered off.
- 6. Press and hold Z Button.
- **7.** Push Thumb Controller forward-moves chair up ramp.
- . CAUTION: Move Controller left or right to adjust chair's direction.
- 9. Release Z Button and place Controller in storage.






- 5. Press and hold Z Button.
- 6. Push Thumb Controller downward; moves chair down ramp.
- 7. CAUTION: Move Controller left or right to adjust chair's direction.
- 8. Release Z Button and place Controller in storage.
- 9. Lock brakes and keep chair powered off.




- 10. Wheelchair facing INQLINE Assist retractors.
- 11. Lock Brakes or power off chair.
- 12. Press and hold buttons (4 sec) to release retractors.
- 13. Detach J-hooks and return them to Stowage.
- 14. Unlock chair and move to proper securement area.





- 10. Press and hold both buttons (4 sec) to release retractors.
- 11. Return J-Hooks to stowage.
- 12. Unlock brakes or power on chair.
- 13. Place chair in secure area.



Contact a Q'Straint® Authorized Dealer or Customer Service (800) 987-9987