

Mechanical Time Switch - 7-Day 120V Mechanical Panel Mount Timer, 56 Trippers

Item PB873MKZ



PRODUCT DESCRIPTION

These timers provide automatic control for pumps, cleaners and other types of loads. Timers have three-way mounting; flush in round opening, raised in rectangular opening or on base. Quick connect terminals for easy installation.

FEATURES

- > Automated control for pumps, cleaners and other types of loads
- ► 3 different mounting methods
- Quick connect terminals for easy installation
- ► 24-hour timing cycle MIN ON time 1-hr, MAX ON time 23-hr, 30-min intervals
- ► 7-day timing cycle 6 to 162-hr ON time, 3-hr intervals

APPLICATIONS

- Motor Control
- Pump Control

TECHNICAL DATA

ա

General		
Model Number	PB873MKZ	
Description	7-Day 120V Mechanical Panel Mount Timer, 56 Trippers	
UPC Code	078275701489	
Brand	Intermatic	
Country of Origin (Intermatic)	MEXICO	
Warranty Period	1-Year limited	
Control Specifications		
Operation Mode	7 day	
Mechanical Specifications		
Captive Trippers	56	
Dimensions		
Draduat Dimanaiana (H x W x D) in		
Product Dimensions (H x W x D) in	3.333 x 2.813 x 1.953 in	
	3.333 x 2.813 x 1.953 in	
Load Ratings	3.333 x 2.813 x 1.953 in	
Load Ratings Motor	3.333 x 2.813 x 1.953 in 1 HP, 16 FLA @ 120 VAC, 60 Hz;2 HP, 12 FLA @ 240 VAC, 60 Hz	
Load Ratings		
Load Ratings Motor	1 HP, 16 FLA @ 120 VAC, 60 Hz;2 HP, 12 FLA @ 240 VAC, 60 Hz	
Load Ratings Motor Resistive Load Ratings Ranges	1 HP, 16 FLA @ 120 VAC, 60 Hz;2 HP, 12 FLA @ 240 VAC, 60 Hz 20 A, 120-277 VAC, 60 Hz	
Load Ratings Motor Resistive Load Ratings Ranges	1 HP, 16 FLA @ 120 VAC, 60 Hz;2 HP, 12 FLA @ 240 VAC, 60 Hz 20 A, 120-277 VAC, 60 Hz	
Load Ratings Motor Resistive Load Ratings Ranges Pilot Duty Load Ratings Ranges	1 HP, 16 FLA @ 120 VAC, 60 Hz;2 HP, 12 FLA @ 240 VAC, 60 Hz 20 A, 120-277 VAC, 60 Hz	
Load Ratings Motor Resistive Load Ratings Ranges Pilot Duty Load Ratings Ranges Electrical Specifications	1 HP, 16 FLA @ 120 VAC, 60 Hz;2 HP, 12 FLA @ 240 VAC, 60 Hz 20 A, 120-277 VAC, 60 Hz 360 VA, 120-240 VAC, 60 Hz	
Load Ratings Motor Resistive Load Ratings Ranges Pilot Duty Load Ratings Ranges Electrical Specifications Wiring Option	1 HP, 16 FLA @ 120 VAC, 60 Hz;2 HP, 12 FLA @ 240 VAC, 60 Hz 20 A, 120-277 VAC, 60 Hz 360 VA, 120-240 VAC, 60 Hz Terminals; (4) 1/4" male (2) for load (2) for independent clock motor	
Load Ratings Motor Resistive Load Ratings Ranges Pilot Duty Load Ratings Ranges Electrical Specifications Wiring Option Input Voltage Range(s)	1 HP, 16 FLA @ 120 VAC, 60 Hz;2 HP, 12 FLA @ 240 VAC, 60 Hz 20 A, 120-277 VAC, 60 Hz 360 VA, 120-240 VAC, 60 Hz Terminals; (4) 1/4" male (2) for load (2) for independent clock motor 120 VAC, 60 Hz	



Packaging		
Unit Carton Dimensions (H x W x L) in	4 x 2.75 x 3 in	
Standards and Certifications		
UL Certification	UL	
California Proposition 65	None	



ACCESSORIES



156PB10398A

107TN221 Trippers - Clip, ON/OFF, 24-Hr for PB and PF1100 Series Red (OFF) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS



107TN222 Turquoise (ON) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS