

Electronic Timer Control - 24-Hour Electronic Time Control, 3-Circuit, Type 3R Plastic Enclosure

Item PE153P



PRODUCT DESCRIPTION

This multipurpose 24-hour control is capable of automatically switching loads according to a preset daily schedule. Controls single- and two-speed pumps and cleaner/booster pumps. Three ON/OFF events per circuit per day.

FEATURES

- Controls single- and two-speed pumps and cleaner/booster pumps
- ► Three ON/OFF events per circuit per day
- Seven preprogrammed modes
- Freeze and heater protection
- ► LCD readout
- Multivoltage input and output
- ► Countdown and override features enable programs to be overridden and automatically resumed without requiring the user to reprogram the system

APPLICATIONS

- Motor Control
- ► Pump Control

TECHNICAL DATA

SP.

General	
Model Number	PE153P
Description	24-Hour Electronic Time Control, 3-Circuit, Type 3R Plastic Enclosure
UPC Code	078275092396
Brand	Intermatic
Country of Origin (Intermatic)	CANADA
Warranty Period	1-Year limited
Control Specifications	
Maximum ON/OFF Operations	3
Operation Mode	24 hour
Mechanical Specifications	
Enclosure Type	Outdoor type 3R plastic
Dimensions	
Product Dimensions (H x W x D) in	9.375 x 5.5 x 3.625 in
Load Ratings	
Tungsten Range(s)	5 A, 120/240 VAC, 50/60 Hz
Motor	80 LRA @ 120 VAC, 50 Hz;80 LRA @ 240 VAC, 50 Hz;17 FLA @ 120 VAC, 50 Hz;17 FLA @ 240 VAC, 50 Hz;80 LRA @ 120 VAC, 60 Hz;80 LRA @ 240 VAC, 60 Hz;17 FLA @ 120 VAC, 60 Hz;17 FLA @ 240 VAC, 60 Hz
Resistive Load Ratings Ranges	17 A, 120/240 VAC, 50/60 Hz
Motor Load Ratings Ranges	80 LRA @ 120/240 VAC, 50/60 Hz; 17 FLA @ 120/240 VAC, 50/60 Hz
Electrical Specifications	



Voltage Selection Type	Multi Voltage
Input Voltage Range(s)	120/240 VAC, 50/60 Hz
Number of Circuits	3
Switch Type	3-SPST
Packaging	
Unit Carton Dimensions (H x W x L) in	4.251 x 7.251 x 11.751 in
Standards and Certifications	
CSA Certification	cCSAus
California Proposition 65	DEHP



ACCESSORIES



178PA28A Freeze Probe Kit, 10k OHM, For MultiWave systems Product Image Not Available

Insulator for 3-Circuit Timers