

Item Bundle - 60 A Load Center with P1353ME Mechanism

Item PE25300



PRODUCT DESCRIPTION

This system can be used as a load center only, or add mechanisms or wiring devices for complete control systems.

FEATURES

- ► Four breaker spaces
- 3-SPST mechanism (P1353ME) controls single- and two-speed filter pumps, cleaner/booster pumps and pool/spa landscape lighting
- ► Load center dead front has two knockouts for switches or GFCls
- ► P1353ME and MultiWave® controllers sold separately
- ► Wiring devices may be installed in these load centers with the use of Standoffs, sold separately
- ► Also compatible with T100 Series

APPLICATIONS

- ► Distribution/Control Panel
- ► Motor Control
- ► Pump Control

TECHNICAL DATA

(1)

| General | |
|--------------------------------|---|
| Model Number | PE25300 |
| Description | 60 A Load Center with P1353ME Mechanism |
| UPC Code | 078275086579 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | CANADA |
| Warranty Period | 1-Year limited |

| Mechanical Specifications | |
|-----------------------------|----------------|
| Number of Breaker Knockouts | 4 |
| Enclosure Type | 3R Beige metal |

| Dimensions | |
|-----------------------------------|--|
| Product Dimensions (H x W x D) in | 16.875 x 10.875 x 4.75 in |
| Knockout Dimensions Bottom | (1) 1 1/8" diameter hole, (6) 1/2" - 3/4", (3) 3/4" - 1" |
| Knockout Dimensions Back | (1) 3/4" - 1" |
| Knockout Dimensions Left | (2) 1/2" - 3/4" |
| Knockout Dimensions Right | (1) 1 3/4" x 2 3/4" |

| waterial Specifications | |
|-------------------------|--|
|-------------------------|--|

Color Beige

| Load Ratings | |
|-------------------------------|----------------------------------|
| Tungsten Range(s) | 5 A, 120/240 VAC, 50/60 Hz |
| Load Center Ratings | 60 A;60 A, 208 VAC, Single Phase |
| Auxiliary Switch | 2 A, 24 VAC |
| Resistive Load Ratings Ranges | 17 A, 120/240 VAC, 50/60 Hz |



Motor Load Ratings Ranges

80 LRA @ 120/240 VAC, 50/60 Hz; 17 FLA @ 120/240 VAC, 50/60 Hz

| Electrical Specifications | |
|---------------------------------------|--------|
| Number of Circuits | 3 |
| Switch Type | 3-SPST |
| Number of Receptacle/Switch Knockouts | 2 |

| Packaging | |
|---------------------------------------|----------------------------|
| Shipping Weight (lbs) | 14.27 |
| Unit Carton Dimensions (H x W x L) in | 6.001 x 17.251 x 12.251 in |

| Standards and Certifications | |
|------------------------------|--------|
| CSA Certification | cCSAus |
| California Proposition 65 | DEHP |



ACCESSORIES



21T166A Spacer-Standoff, 3" long - 2 pack



21T156A Spacer-Standoff, 3" long - 4 pack