

Freeze Protection Control - Freeze Protection Thermostat only for 120/240V Applications, Type 3R Metal Enclosure

Item PF1103



PRODUCT DESCRIPTION

Protects pool/spa equipment against freeze damage. Turns pump and heater on when the outdoor temperature drops. Integrated adjustable thermostat.

FEATURES

- > Turn pump and heater ON when outdoor temperature drops below user-adjustable setpoint on thermostat
- Models with or without mechanical timer mechanism
- ► Heavy-duty metallic rainproof enclosure
- ► For use with pool and spa, pond, fountain or marina type applications

APPLICATIONS

- Protection
- Pump Control

TECHNICAL DATA

SP.

Model NumberPF1103DescriptionFreeze Protection Thermostat only for 120/240V Applications, Type 3R Metal EnclosureUPC Code078275040571BrandIntermaticCountry of Origin (Intermatic)MEXICOWarranty Period1-Year limitedMechanical SpecificationsUnited StatemarkFinclosure TypeOutdoor type 3R metalDimensionsHx Wx D) inProduct Dimensions (Hx W x D) in9.625 x 5.75 x 3.625 in	
UPC Code 078275040571 Brand Internatic Country of Origin (Internatic) MEXICO Warranty Period 1-Year limited Mechanical Specifications URICO Fnclosure Type Outdoor type 3R metal Dimensions HIMING Product Dimensions (H x W x D) in 9.625 x 5.75 x 3.625 in	
Brand Internatic Country of Origin (Intermatic) MEXICO Warranty Period 1-Year limited Mechanical Specifications Undoor type 3R metal Enclosure Type Outdoor type 3R metal Pimensions 9.625 x 5.75 x 3.625 in	
Country of Origin (Intermatic) MEXICO Warranty Period 1-Year limited Mechanical Specifications	
Warranty Period 1-Year limited Mechanical Specifications	
Mechanical Specifications Enclosure Type Outdoor type 3R metal Dimensions Product Dimensions (H x W x D) in 9.625 x 5.75 x 3.625 in	
Enclosure Type Outdoor type 3R metal Dimensions Product Dimensions (H x W x D) in 9.625 x 5.75 x 3.625 in	
Enclosure Type Outdoor type 3R metal Dimensions Product Dimensions (H x W x D) in 9.625 x 5.75 x 3.625 in	
Dimensions Product Dimensions (H x W x D) in 9.625 x 5.75 x 3.625 in	
Product Dimensions (H x W x D) in 9.625 x 5.75 x 3.625 in	
Product Dimensions (H x W x D) in 9.625 x 5.75 x 3.625 in	
Knockout Dimensions Bottom (2) 1/2" - 3/4"	
Knockout Dimensions Back (4) 1/2" - 3/4", (1) 1/2" - 3/4"	
Knockout Dimensions Left (1) 1/2" - 3/4"	
Knockout Dimensions Right(1) 1/2" - 3/4"	
Load Ratings	
Motor 1 1/2 HP @ 120 VAC, 3 HP @ 240 VAC, 60 Hz	
Packaging	
Unit Carton Dimensions (H x W x L) in 4 x 7.06 x 11.5 in	
	_
Operating Specifications	
Thermostat Range Minimum (°C) 0.5	
Thermostat Range Minimum (°F) 33	
Thermostat Range Maximum (°C) 6	
Thermostat Range Maximum (°F) 42	



Standards and Certifications	
CSA Certification	cCSAus
California Proposition 65	DEHP



ACCESSORIES



107TN222

Turquoise (ON) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS



107TN221 Red (OFF) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS