

Load Center - 60 A Load Center Only, 4-Breaker Spaces

Item T21000R



PRODUCT DESCRIPTION

This system can be used as a load center only, or add a heavy-duty mechanical time switch or wiring devices for a complete system.

FEATURES

- ► Four breaker spaces
- ► Accepts PF1000M, P1403ME, P1353ME, P4043ME, P4243ME, T100M or RC2000M Series mechanisms
- Accepts many interchangeable type breakers
- Load center dead front has two knockouts for switches or GFCIs and one on the side
- ► Wiring devices may be installed in these Load Centers with the use of Standoffs, sold separately

APPLICATIONS

- Distribution/Control Panel
- ► Motor Control
- Pump Control

TECHNICAL DATA

SP.

General	
Model Number	T21000R
Description	60 A Load Center Only, 4-Breaker Spaces
UPC Code	078275086913
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Mechanical Specifications	
Number of Breaker Knockouts	4
Dimensions	
Product Dimensions (H x W x D) in	16.875 x 8.875 x 4.75 in
Knockout Dimensions Bottom	(5) combination 1/2" - 3/4" and (3) combination 3/4" - 1"
Knockout Dimensions Back	(1) combination 1/2" - 3/4" and (1) 3/4" - 1"
Knockout Dimensions Left	(1) combination 1/2" - 3/4"
Knockout Dimensions Right	(1) 1 3/4" x 2 3/4"
Load Ratings	
Mechanisms	Load Center Only
Electrical Specifications	
Number of Receptacle Knockouts	2
Packaging	
Unit Carton Dimensions (H x W x L) in	5.75 x 10 x 17.75 in
Standards and Certifications	



CSA Certification	cCSAus
California Proposition 65	None



ACCESSORIES



156T1978AMX 1 Set of ON/OFF Trippers for T100, T7000, and WH40

156T1978A Extra/replacement trippers 1 ON and 1 OFF Product Image Not Available

124--00066 Insulator for 3-Circuit Timers



21T166A Spacer-Standoff, 3" long - 2 pack



21T156A Spacer-Standoff, 3" long - 4 pack



156T2978A Package Accessory Trippers



22T338GR Mounting Bracket for Intermatic Standardized Timer Mechanisms