PENTAIR

TRITON® II
FIBERGLASS SAND FILTER

Efficient, dependable filtration for your pool.

The Triton II Filter is the result of over 40 years of product evolution and refinement. It has set the industry standard for effectiveness, efficiency, long runs between service and years of dependable, low-maintenance operation.

The Triton II Filter features a special internal design that keeps the sand bed level, ensuring even water flow and resulting in the most efficient filtration possible.

PENTAIR.COM

TRADEGRADE

TRITON® II FIBERGLAS SAND FILTER

The best reputation in the industry for all the right reasons.

Besides its filtration performance, the Triton II Filter delivers a level of dependability and ease of operation and maintenance. Every design detail has been refined to make the Triton II Filter the industry standard.

KEY FEATURES

Heavy-duty closure
For easy access with built-in pressure relief valve, making inspection and maintenance faster and easier.

Swing-away water diffuser
Allows instant access to sand and all internal parts.

Combination sand-and-water drain
Speeds servicing and winterizing.

GlasLok™ process one-piece fiberglass-reinforced tank
UV-resistant surface finish for years of dependable, corrosion-resistant, unequaled strength and durability.

Flow system design
Controls filtration quality and helps ensure maximum run times between backwashing to save you time.

Threaded internal parts
For ease of maintenance.

Threaded bulkhead connectors
For easier installation and service.

Time-proven internal design
Ensures that all water receives maximum filtration for crystal-clear results.

Model Number	Filter Area Sq. Ft.	Vertical Clearance*	Filter Diameter	Required Sand** (lbs.)	Flow Rate GPM (Comm.)	Turnover Capacity–Res. (Gallons)		
						8 hrs.	10 hrs.	12 hrs.
TR 40	1.92	32.5"	19"	175	38	18,240	22,800	27,360
TR 50	2.46	36.75"	21"	225	49	23,520	29,400	35,280
TR 60	3.14	37.5"	24"	325	63	30,240	37,800	45,360
TR 100	4.91	41.75"	30"	600	74	35,520	44,400	53,280
TR 140	7.06	47.25"	36"	925	106	50,880	63,600	76,320

*Required clearance to remove the closure.

**Use standard #20 silica sand.

PENTAIR

TRADEGRADE

The TradeGrade family of products is exclusively made for and sold by the world's most demanding pool professionals.

400 Regency Forest Dr | Cary, NC 27518 | United States | 800.831.7133 | pentair.com

Certified to NSF/ANSI Standard 50