











CAP® Closed end blind rivets

Alu/stainless steel Standard

 Aluminium alloy
 Stainless steel





| D | D x L mm |  mm | No. |  |
|--|-------------------|--|-----------------|---|
| 3.2  3.3 mm | 3.2 x 6.5 | 0.5 - 2.0 | 143 3437 | A 500 |
| | 3.2 x 8.0 | 2.0 - 3.5 | 143 3438 | " |
| | 3.2 x 9.5 | 3.5 - 5.0 | 143 3439 | " |
| | 3.2 x 10.5 | 5.0 - 6.5 | 143 3440 | " |
| | 3.2 x 12.5 | 6.5 - 8.0 | 145 3890 | " |
| 4  4.1 mm | 4 x 8.0 | 0.5 - 3.5 | 143 3441 | B 500 |
| | 4 x 9.5 | 3.5 - 5.0 | 145 3891 | " |
| | 4 x 11.0 | 5.0 - 6.5 | 145 3892 | " |
| | 4 x 12.5 | 6.5 - 8.0 | 143 3442 | " |





| D | D x L mm |  mm | No. |  |
|--|-------------------|--|-----------------|---|
| 4.8  4.9 mm CE | 4.8 x 8.0 | 1.0 - 3.5 | 143 3443 | B 500 |
| | 4.8 x 9.5 | 3.5 - 5.0 | 143 3444 | " |
| | 4.8 x 11.0 | 5.0 - 6.5 | 143 3445 | " |
| | 4.8 x 12.5 | 6.5 - 8.0 | 143 3446 | " |
| | 4.8 x 14.0 | 8.0 - 9.5 | 143 3447 | " |
| | 4.8 x 16.0 | 9.5 - 11.0 | 143 3448 | " |
| | 4.8 x 18.0 | 11.0 - 13.0 | 143 3449 | " |
| | 4.8 x 21.0 | 13.0 - 16.0 | 143 3450 | B 250 |




Material surcharge will be added at a daily rate

A2 stainless steel Standard

 Stainless Steel A2 — no. 1.4301
 Stainless Steel A1



| D | D x L mm |  mm | No. |  |
|--|-------------------|--|-----------------|---|
| 3.2  3.3 mm | 3.2 x 6.0 | 0.8 - 2.0 | 145 3899 | A 500 |
| | 3.2 x 8.0 | 2.0 - 4.0 | 143 3452 | " |
| | 3.2 x 10.0 | 4.0 - 6.0 | 145 3900 | " |
| | 3.2 x 12.0 | 6.0 - 8.0 | 143 3453 | " |
| 4  4.1 mm | 4 x 6.0 | 0.8 - 1.5 | 145 3901 | A 500 |
| | 4 x 8.0 | 1.5 - 3.5 | 143 3454 | " |
| | 4 x 10.0 | 3.5 - 5.5 | 145 3902 | B 500 |
| | 4 x 12.0 | 5.5 - 7.5 | 143 3455 | " |
| | 4 x 16.0 | 7.5 - 11.5 | 145 3903 | " |

| D | D x L mm |  mm | No. |  |
|--|-------------------|--|-----------------|---|
| 4.8  4.9 mm | 4.8 x 8.0 | 0.8 - 3.0 | 143 3456 | B 500 |
| | 4.8 x 10.0 | 3.0 - 5.0 | 143 3457 | " |
| | 4.8 x 12.0 | 5.0 - 7.0 | 143 3458 | " |
| | 4.8 x 16.0 | 7.0 - 11.0 | 143 3459 | " |
| | 4.8 x 20.0 | 11.0 - 15.0 | 143 3460 | B 250 |

Material surcharge will be added at a daily rate
 You have to expect limited jaw life.



The information on shear and tensile strength, rivet pin diameters and the maximum setting head diameters can be found on **page 45**