

FIRE DOOR COMPLIANCE VERIFICATION

Important! This information sheet must be completed in full to obtain certification.

Project

Project address

Builders Name

Address

Contact Phone

Door Numbers

WALL

<input type="checkbox"/>	MASONRY	STUD MATERIAL
<input type="checkbox"/>	STUD FRAME	STUD SIZE
		WALL SHEETING

DOOR FRAME

<input type="checkbox"/>	INSTALLED IN ACCORDANCE WITH FIRE DOOR APPROVAL	
<input type="checkbox"/>	51 X 25 REBATE	<input type="checkbox"/> 41 X 25 REBATE

DOOR CLEARANCES

<input type="checkbox"/>	TOP & SIDES MAXIMUM 3mm
<input type="checkbox"/>	BOTTOM MAXIMUM 10 mm MINIMUM 3 mm

FIRE RATING

<input type="checkbox"/>	/60/30 (1 HOUR)	SIZE
<input type="checkbox"/>	/120/30 (2 HOURS)	SIZE
<input type="checkbox"/>	/180/30 (3 HOURS)	SIZE
<input type="checkbox"/>	/240/30 (4 HOURS)	SIZE

HARDWARE MANUFACTURER & MODEL No. MUST BE SPECIFIED!

<input type="checkbox"/>	LOCKSET/LATCHSET
<input type="checkbox"/>	OTHER
<input type="checkbox"/>	LATCHBACKSET
<input type="checkbox"/>	DOOR CLOSER
<input type="checkbox"/>	CLOSER BACKCHECK

PAIR OF DOORS

<input type="checkbox"/>	HEAD LATCH
<input type="checkbox"/>	AUTOFLUSH BOLTS
<input type="checkbox"/>	SEQUENCE SELECTOR
<input type="checkbox"/>	ALUMINIUM MEETING STILES

Important! ONLY TESTED AND APPROVED HARDWARE CAN BE FITTED TO FIRE DOORS.

OPERATION DOOR CLOSED TO FULLY LATCHED POSITION (DOOR MUST LATCH FULLY UNASSISTED).

I the undersigned, declare that the above information is true and correct.
The fire door assembly must comply with as/n7s 1905.1:1997 before certificate can be issued.

SIGNED..... DATE..... ON BEHALF OF.....